



HNC516-ODA



FEATURES

6MP Motorized IR Vandal-Proof Dome, Exterior

- 1/1.7" Progressive Scan CMOS
- Up to 6 Megapixel (3072 × 2048) High Resolution
- 6MP Real-time Video
- Day / Night
- Audio 1/1 and Alarm 1/1
- Vandal-proof Housing
- Motorized VF Lens

| Specifications | |
|-----------------------|--|
| Model Number | HNC516-ODA |
| Image Sensor | 1/1.7" progressive scan CMOS |
| Min. illumination | 0.01 lux@F1.2, AGC ON, 0 lux with IR |
| Shutter time | 1/25s ~ 1/100,000s |
| Lens | Motorized VF lens, 2.8 ~ 12 mm @F1.4, angle of view: 96° ~ 32° |
| Auto iris | DC drive |
| Angle adjustment | Pan: 0° ~ 355°, Tilt 0° ~ 75°, Rotation 0 ~ 355° |
| Day & night | IR Cut filter with auto switch |
| Wide Dynamic Range | True WDR |
| Video compression | H.264+ / H.264 / MJPEG |
| Bit rate | 32 Kbps ~ 16 Mbps |
| Max, image resolution | 6MP CMOS, (3072 × 2048) |

| Specifications | |
|-------------------------|--|
| Frame rate | 24fps(3072 × 2048) |
| Network storage | NAS |
| System compatibility | ONVIF, PSIA, CGI |
| Communication interface | 1 RJ45 10M / 100M Ethernet port and 1 RS-485 interface |
| Video output | 1 Vp-p composite output (75 Ω / RCA) |
| On-board storage | Built-in SD slot, up to 128 GB |
| Reset button | Yes |
| Operating conditions | -30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing) |
| Power supply | DC 12V, AC 24V +/- 10%, PoE (802.3af) |
| Power consumption | 12W |
| Impact protection | IK10 |
| IR range | 120 feet |
| Dimensions | Ø 6.29" x 5" |
| Weight | 2100g (4.62 lbs) |
| Wall Mount | HTH-273ZJ-DM26B |
| Pendant Mount | HTH-268ZJ |
| Corner and Pole | C:HTH-276ZJ, P:HTH-275ZJ |