

HNC518-IDA



FEATURES

8MP Motorized IR Vandal-Proof Dome, Indoor

- 1/1.7" Progressive Scan CMOS
- Up to 8 Megapixel (4096 × 2160) High Resolution
- 8MP Real-time Video
- Day / Night
- Audio/Alarm IO
- Vandal-proof Housing
- Motorized VF Lens

Specifications	
Model Number	HNC518-IDA
Image Sensor	1/1.7" progressive scan CMOS
Min. illumination	0.01Lux @ (F1.2, AGC ON), 0.014Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter time	1s ~ 1/100,000s
Lens	2.8~12mm @ F1.4, angle of view: 96.0°~32.6°
Auto iris	DC drive
Angle adjustment	Pan: 0° ~ 355°, Tilt 0° ~ 75°, Rotation 0 ~ 355°
Day & night	ICR
Wide Dynamic Range	True WDR
Video compression	H.264 /H.264+/ MJPEG
Bit rate	32 Kbps ~ 16 Mbps
Max, image resolution	8MP CMOS,(4096 × 2160)

Specifications	
Frame rate	22fps(4096×2160)24fps(3840×2160,1920×1080,1280×720)
Network storage	NAS (Support NFS,SMB/CIFS), ANR
System compatibility	ONVIF, PSIA, CGI
Communication interface	1 RJ45 10M / 100M /1000m Ethernet port, 1 RS-485 interface
Video output	1Vp-p composite output (75 Ω/BNC)
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to128GB
Reset button	Yes
Operating conditions	-30°C-60 °C (-22 °F-140 °F), Humidity 95% or less(non-condensing)
Power supply	12 V DC ± 10%, PoE (802.3at)
Power consumption	Max. 9W
Impact protection	IK10
IR range	Up to 100ft.
Dimensions	Φ 140×121.8mm (Φ 5.51" ×4.80")
Weight	1400 g (3.09lbs)