

HNC6D54-IZS



FEATURES

EXIR Flexible PanoVu Network Camera

- 24fps @ 2560 x 1920
- H.265, H.265+, H.264, H.264+
- 30 to 90ft IR Range
- IP67, IK10
- 4 Flexible Lens
- 6 behavior analysis, 4 exception detection, and face detection

Specifications	
Model Number	HNC6D54-IZS
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.006 Lux @ F1.2, 0 Lux with IR
Shutter Speed	1 - 1/100,000s
Auto-iris	N/A
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	120 dB
3-Axis Adjustment	Four flexible lens in one track, slide range: -180° to 180°, tilt: 0° to 135°, rotate: 0° to 355°
Focal Length	2.8mm - 12mm
Aperture	F1.6
FOV	Horizontal field of view: 30° to 96.3° Vertical field of view: 17° to 54° Diagonal field of view: 34° to 121°

Specifications	
IR Range	30ft to 90ft
Wave Length	850nm
Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub stream: H.265/H.264/MJPEG Third stream: H.265/H.264
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/AAC
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)/16-64Kbps(AAC)
Behavior Analysis	Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection
Max. Resolution	2560 x 1920
Frame Rate	24fps @ 2560 x 1920
Audio I/O	1/1
Alarm I/O	2/2
On Board Storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
Communication Interface	1 RJ45 10M/100M/1000M Ethernet port 1 RS-485 interface (-S)
Material	Aluminum alloy, engineering plastics
Protection Level	IK10, IP67
Power Supply	12VDC, PoE
Power Consumption	Max. 17W
Working Temperature	-30°C to 60°C (-22°F to 140°F)
Dimensions	Ø11.42" × 5.73"
Weight	10.3lbs
Wall Mount	HTH-602ZJ
Pendant Mount	HTH-661ZJ
Pole Mount	HTH-275ZJ
Corner	HTH-276ZJ