

HNRT00-128I16I24



FEATURES

128 Channel Network Video Recorder with Raid support

- Up to 128 Ch. IP cameras input
- 576 Mbps bit rate input max
- Power Redundancy
- Up to 12MP resolution recording
- VGA output up to 1080p, HDMI output up to 4K resolution
- 4 Self-adaptive 10M/ 100M/ 1000M network interfaces
- 16 or 24 SATA HDD interface up to 8TB each

Specifications	
Model Number	HNRT00-128/I16(I24)
Video Compression	H.265, H.264+, H.264, MPEG4, MJPEG (Hunt IP Cameras Only)
IP Video Input	128 Ch. 576 Mbps max input
Video Output	2 HDMI, 1 VGA
RAID	0, 1, 5, 6, 10, 50, 60, JBOD
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	12fps @ Up to 12 Megapixels
HDMI Output Resolution	4K resolution 4096×2160@ 30Hz
VGA Output Resolution	1080P,60Hz
Synchronous Playback	16 Ch.
Network Interface	4 RJ45 10M/100M/1000M

Specifications	
PoE Network Interfaces/Built-in switch	N/A
Internal SATA	I16: 16 SATA up (up to 8TB each) I24: 24 SATA up (up to 8TB each)
Alarm In/out	16/8
eSATA	N/A
USB interface	2 x USB2.0, 2 x USB3.0
Operation Temperature	0 °C ~ +50 °C (32°F ~ 122°F)
Chassis	3U
Dimension	F16: 17.4"W x 19.4"D x 5.7"H F24: 17.4"W x 20.8"D x 6.8"H
Power Supply	F16: 100 ~ 240 VAC, Max 550W, Redundancy F24: 100 ~ 240 VAC, Max 550W, Redundancy
Weight	F16: 41 lbs F24: 59 lbs