



SPECIFICATION

Model NO.	HT-B8SCFKE28-X
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps
Camera	
Image Sensor	1/2.5" CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Minimum Illumination	0.01Lux
Scanning System	Progressive Scan
Lens	
Focus Length	2.8mm
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
IR Cut Filter	YES
Infrared LED	14μ x 20PCS
Infrared Distance	up to 30m
IR Status	AGC Auto Control
Camera Features	
Starlight	N/A
Day/Night	YES/NO
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	2DNR
Coaxial Audio	YES(only TVI)
White Balance	AUTO / MANUAL
Gain Control	AUTO
General	
Housing	Metal, IP67
Bracket	NO

Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	Φ 171 x 73(H) x73(D) mm
Weight	750g