



30X Day & Night 30fps Full HD PTZ Dome IP Camera



Features

- Power over Ethernet+
- Pan-tilt-zoom capabilities
- 30X optical zoom
- IR cut filter for day/night operations
- 1080p HD resolution
- Wide Dynamic Range up to 90dB

Description

The IPS5300EA is 1080P Full HD PTZ Dome IP camera. The high-speed domes are capable of streaming HD video at up to 30 FPS. Featuring LILIN's Wide dynamic Range (WDR) feature, the IPS5300EA captures highlights and shadows simultaneously, eliminating pixilation and smear. Combine this with 3D Noise Reduction technology and adaptive tone reproduction and the contrast of images in bright or dark areas is dramatically improved. Capable of making 360° continuous rotations with a speed range of 0.15°□360° per second, users can accurately position the camera to identify specific targets. The 30x optical zoom and 16x digital zoom capacity give the IPS5300EA an impressive range. The camera can be powered through High Power over Ethernet, which complies with the PoE standard IEEE 802.3at.

Specifications

Model	IPS5300EA
Pick Up Element	1/2.8" Type CMOS Sensor
Effective pixels	1956 (H) × 1266 (V) = 2,476,296 (pixels) ; Effective pixels : 1944 (H) × 1224 (V) = 2,379,456 (pixels)
Video Compression	H.264 , Motion JPEG
Resolution	1080P (1920 x 1080) , 720P (1280 x 720) , D1 (720 x 480, 720 X 576) , CIF (352 X 240)
Frame Rates	H.264: up to 30FPS @ 1920 x 1080 ; Motion JPEG: up to 30FPS @ 720 x 480
Lens	4.3 mm (WIDE)-129.0 mm(TELE)
Angle of View	Approx. 64.45°(H) 39.27°(V) (WIDE end), approx. 2.41°(H) 1.36°(V) (TELE end), (1080p mode)
Minimum object distance	10 mm (WIDE end), 1.5m (TELE end)
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast
Video bitrate	128 Kbps to 8 Mbps ; Frame rate and bitrate controllable on-the-fly ; VBR / CBR / GOP supported
Scanning System	Progressive scan

Min. illumination/Low Light Mode (Colour)	0.5 lux (1/30 sec, F1.6(Wide), 50 IRE, AGC-Gain:30dB ICR-OFF Color mode) 0.1 lux (1/30 sec, F1.6(Wide), 50 IRE, AGC-Gain:30dB ICR-ON B/W mode) 0.2 lux (1/8 sec, F1.6(Wide), 50 IRE, AGC-Gain:30dB ICR-OFF Color mode) 0.01 lux (1/8 sec, F1.6(Wide), 50 IRE, AGC-Gain:30dB ICR-ON B/W mode)
White Balance	ATW/Indoor(3200K)/Outdoor(5800K) /Manual(1800K -10500K)
Back Light Compensation (BLC)	Off / BLC / WDR
Electrical Shutter	Auto / manual(1/1 to 1/100,000)
Auto Gain Control	0 - 30dB
3D Noise Reduction	Off / On (2D, 3D)
Privacy Masking	Off / On (up to 16 areas)
Live Video Output	CVBS 1.0 Vp-p / 75 Ω BNC
Panning Range	360° Endless
Panning Speed	Manual approx. 0.15°/s - 120°/s 8 Steps, Preset approx. 1°/s - 255°/s, Alarm Trigger Speed 360°/s
Panning Mode	Manual, Auto, Manual Position, Sequential Position
Tilting Range	-6°- 96°
Tilting Speed	Manual approx. 0.15°/s - 120°/s 8 Steps, 16 Steps / Preset approx. 1°/s - 255°/s, Alarm Trigger Speed 360°/s
Tilting Mode	Manual, Auto, Manual Position, Sequential Position
Minimum Aperture Ratio	1:1.6 (WIDE)-5.0 (TELE)
Control Function	Pan and Tilt / Zoom and Focus / Iris and ICR / 128 Preset Position / Home Position
Zoom Speed	0 - 7 Selectable[Fast : Approx. 6.0 Second (Tele to Wide) in Manual Mode]
Focus Speed	0 - 7 Selectable [Fast : Approx. 6.0 Second (Far to Near) in Manual Mode]
Exposure Mode	Auto / Manual

Auto Mode	Off / AUTO / SEQ / TOUR
PTZ Control	Pan, tilt, zoom-in / zoom-out, absolute position, and mouse click function
Schedule Setting	Off / Auto Mode / Preset position
Encryption	Base64 HTTP encryption
Access	Multiple user access levels with password protection
Max number of online users	10 user accounts available
Multi IP address	Yes
User accounts	10 simultaneous users
Alarm event triggers	Alarm / motion / audio / Network lost detection
Alarm event actions	FTP, HTTP post, SD card
CPU	Embedded SoC ARM11, 528MHz, 256MB DDR2, 256MB flash memory
Network Interface/Ethernet	10Mbps / 100Mbps, RJ-45
CE	Yes, EMI CLASS A
FCC	Yes, EMI CLASS A
Web browser	Microsoft® Internet Explorer® 9.0 and later
Protocols	IPv4, IPv6, TCP, UDP, HTTP, SMTP, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, Telnet, RTSP, RTCP, ONVIF profile S, SNMP, Bonjour
Video Management	ONVIF Profile S / LILIN Navigator Enterprise 1.0 and 2.0 / Third party VMS through LILIN HTTP API
Video Display	LILIN Universal ActiveX & LILIN Java Applet
OS	Embedded Linux 2.6.32
Audio	2-way audio G.711
SD Card (recording)	Support Micro SD/SDHC/SDXC card for circular recording (card is not included)
Mobile phone	Integrated to LILIN mobile app (LILINViewer) , iPhone, iPad, Android support
Alarm Input / output	6 Input (TTL 5Vdc) , 2 Output (0.5A 120Vac, 1A 24Vac)
Operating temperature	-10°C - + 50°C (14°F-122°F)

Operating humidity	0%-90%
Dimensions	(H x D) 245mm x 155mm
Weight	2300g approx.
Power Supply	AC100 - 240V \pm 10%
Power Consumption	AC100 - 240V, 16W
