

MAR7504



FEATURES

4 CH TVI Mobile DVR

- User-friendly GUI providing easy and flexible operations.
- Supports connecting high-definition TVI camera.
- 4 analog channels of audio & video inputs connectable; each channel supports up to 720p resolution with H.264 encoding technology.
- Two HDD/SSD hard disks with 1T capacity can be plugged for data storage.
- Specialized aviation connectors ensuring signal stability.
- Ignition start, delay (0 to 6h) shutdown and 24-hour scheduled startup/shutdown.
- Software-based firewall supported.

| Specifications | |
|---------------------|--|
| Model Number | MAR7504 |
| Video compression | H.264 |
| Analog Video input | 4-ch; Aviation plug (1.0 Vp-p, 75 Ω) |
| Audio input | 4-ch; Aviation plug (linear level, 1kΩ) |
| Encoding resolution | Main stream: 720p/WD1/4CIF/CIF; Sub-Stream: CIF/QCIF |
| Frame rate | 1 to 30fps |
| Audio input | 4-ch, RCA (2.0 Vp-p, 1 KΩ) |
| Audio compression | G.711 |
| Stream type | Video, Video & Audio |
| Dual stream | Supported |
| HDD Type | 2 × 2.5 inch hard disk (HDD/SSD) |
| HDD Capacity | Up to 1TB each |

| Specifications | |
|----------------------------|--|
| Two-way audio | G.722 |
| Sensor-in | 4 high/low level signal inputs |
| Alarm input | 3-ch high/low level signal input |
| Alarm output | 2-ch relay signal output |
| Network interface | 1 × 10M/100M self-adaptive RJ45 Ethernet interface |
| Serial interface | 2 × RS-232, 1 × RS-422 |
| USB port | 1 × standard USB 2.0 in front panel; 1 × aviation plug USB 2.0 in rear panel |
| SIM card | 1 SIM/UIM card slots |
| Operating system | Linux |
| Operating method | Mouse, IR remote control, and Web control |
| Power supply | Input: 8 to 36 VDC; Output: 12 VDC/1 A, 5 VDC/1 A |
| Consumption | ≤ 20 W |
| Working temperature | -25° C to +70° C (-13° F to 158° F) |
| Working humidity | 10% to 90% |
| Dimensions (W×D×H) | 202 × 85.5 × 253 (7.95 × 3.37 × 9.96") |
| Weight (without HDDs/SSDs) | Approx. 3 kg (6.61 lb) |