



## S Series

# MD9560-DH-V2 (2.8 mm)

2MP Mobile Dome Network  
Camera



## Technical Specifications

System Information	
CPU	Multimedia SoC (System-on-Chip)
Flash	256MB
RAM	512MB

  

Camera Specifications	
Image Sensor	1/2.8" Progressive CMOS
Max. Resolution	1920x1080
Lens Type	Fixed-focal
Focal Length	f = 2.8 mm
Aperture	F2.0
Iris Type	Fixed-iris
Field of View	114° (Horizontal) 61° (Vertical) 135° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut filter	Yes
Illuminators	Built-in IR illuminators, effective up to 20 meters with Smart IR, IR LED*2
Minimum Illumination	0.13 lux @ F1.8 (Color) 0.01 lux @ F1.8 (B/W) 0 lux with IR illumination on
Pan Range	±30°

Tilt Range	90°
Rotation Range	±180°
Pan/Tilt/Zoom Functionalities	48x digital zoom (4x on IE plug-in,12x built-in)
Storage	Micro SD/SDHC/SDXC card slot Seamless Recording
Built-in Installation Aids	Pixel calculator

Video	
Compression	H.265, H.264, MJPEG
Maximum Frame Rate	60 fps @ 1920x1080
Maximum Streams	4 simultaneous streams
Main Stream	60fps @1920x1080, 1600x904, 1360x768, 1280x720, 640x360, 480x272
2nd Stream	60fps @1920x1080, 1600x904, 1360x768, 1280x720, 640x360, 480x272
3rd Stream	60fps @1920x1080, 1600x904, 1360x768, 1280x720, 640x360, 480x272
S/N Ratio	60 dB
Dynamic Range	120dB
Video Streaming	Adjustable resolution, quality and bitrate; Smart Stream III
Image Settings	<p>General settings video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings</p> <p>Illuminators illuminators, anti-overexposure</p> <p>Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR, scene mode (auto, deblur)</p> <p>Exposure BLC, HLC, exposure control (exposure level, iris adjustment, exposure time, gain control, iris mode), AE speed adjustment, WDR</p> <p>Focus zoom, focus</p> <p>Privacy mask pixel calculator Scheduled profile settings</p>

Audio	
Audio Capability	One-way Audio
Compression	G.711, G.726, MPEG-2 AAC-LC
Interface	Built-in microphone External microphone Input
Effective Range	5 meters

Network	
Users	Live viewing for up to 10 clients
Security	Access list, digest authentication, HTTPS , IEEE 802.1x, Password protection,Trend Micro IoT Security (brute force attack event, cyberattack event, quarantine event), user access log, user account management

Protocols	802.1X, ARP, CIFS/SMB, CoS, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, QoS, RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS, UDP, UPnP
Interface	10Base-T/100 BaseTX Ethernet (M12, Female, 4pin D-coded)
ONVIF	Profile G, S, T supported, specification available at <a href="http://www.onvif.org">www.onvif.org</a>

## Solution Integration

VADP Package	Trend Micro (3-year free trial)
Video Motion Detection	Five-window video motion detection

## Alarm and Event

Event Trigger	Motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection, SD card life expectancy, Cybersecurity events (Brute force attack event, Cyberattack event, Quarantine event)
Event Action	Event notification via digital output, email, HTTP, FTP, NAS server, SD card File upload via email, HTTP, FTP, NAS server, SD card

## General

Connectors	M12 for Network connection*1 Audio Input*1 Digital input*1 (30V) Digital output*1 (12V, 50mA) DC power input*1
LED Indicator	System power and status indicator
Power Input	DC 7.5~48V
Power Consumption	Max. 5.4W(IR ON) Max. 3.56W(IR OFF)
Dimensions	98 x 54 x 110mm
Weight	approx. 384 g
Casing	IP67, IP66, IK10, NEMA 4X
Certifications	EMC CE (EN 55032, EN 55024 Class B, EN 50121-4, EN 50121-3-2), FCC (FCC Part 15 Subpart B Class B), RCM (AS/NZS CISPR 32 Class B), VCCI (VCCI-CISPR 32 Class B)  Safety UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 60950-22, IEC/EN 62471)  Environment IK10, IP66/67, NEMA 4X  Railway EN 50155: 2021(OT1, 24V DC), EN 50121-3-2:2016, EN 60068-2-1:2007, EN 60068-2-2:2007, EN 61373:2010, EN 45545-2, IEC 60571 Ed 3.0, IEC 62236-3-2 Ed 3.0, EN50121-4:2016  Vehicles ECE R118, R10
Operating Temperature	Starting Temperature: -25°C ~ 55°C Working Temperature: -25°C ~ 60°C(IR OFF) -25°C ~ 55°C(IR ON)
Humidity	98% RH (non-condensing)
Storage Temperature	-40°C ~ 70°C (14°F ~ 158°F)

## System Requirements

Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above
Other Players	VLC: 1.1.11 or above

<b>Included Accessories</b>	
Packing Contents	Quick installation guide, screw driver, alignment sticker