

MNR5504-GW



FEATURES

4 CH IP Mobile DVR

- User-friendly GUI providing easy and flexible operation.
- Supports 4 IP Cameras through PoE ports on back.
- 4 IP channels of audio & video inputs; each channel supports up to 1080p resolution with H.264 encoding technology.
- Two HDD/SSD with 1T capacity can be installed for data storage.
- Ignition start, delay (0 to 6h) shutdown and 24-hour scheduled startup/shutdown.
- Software-based firewall.

Specifications	
Model Number	MNR5504/GW
Video compression	H.264
IP Video input	4-ch
Audio input	4-ch
Encoding resolution	Main stream: 1080p/720p/WD1/4CIF/CIF; Sub-Stream: CIF/QCIF
Frame rate	1 to 30fps
Audio Output	2-ch
Audio compression	G.711
Stream type	Video, Video & Audio
Dual stream	Supported
HDD Type	2 × 2.5 inch hard disk (HDD/SSD)
HDD Capacity	Up to 1TB each

Specifications	
Two-way audio	G.722
Sensor-in	4 high/low level signal inputs
Alarm input	3-ch high/low level signal input
Alarm output	2-ch relay signal output
Network interface	1 × 10M/100M self-adaptive RJ45 Ethernet interface
Serial interface	1 × RS-232, 1 × RS-422
USB port	1 × standard USB 2.0 in front panel; 1 × aviation plug USB 2.0 in rear panel
SIM card	1 SIM/UIM card slots
Operating system	Linux
Operating method	Local Operation, IR remote control, and Web control
Power supply	Input: 8 to 36 VDC; Output: 12 VDC/1 A, 5 VDC/1 A
Consumption	≤ 20 W
Working temperature	-10° C to +55° C (14° F to 131° F)
Working humidity	10% to 90%
Dimensions (W×D×H)	7" x 6.7" x 2"
Weight (without HDDs/SSDs)	Approx. 1.6 kg (3.53lb)