



1080P Day & Night Fixed IR IP Mini Dome Camera



Features

- Full HD 2 megapixel CMOS image sensor
- 1080P True H.264 AVC High Profile video compression
- H.264 and Motion JPEG multi-profile video streaming
- Smart H.264 supported
- 3D noise reduction (MCTF)
- 2D WDR function
- HDR function up to 100dB
- Digital PTZ supported
- IVS supported
- Tampering / Motion detection alarm function
- High efficiency IR LED, radiant distance up to 30m
- Day & Night (IR cut removable)
- Built-in highly sensitive microphone
- ONVIF Profile S supported
- IP67 rain and dust resistant

Description

Especially design for little space concern, MR6822 provide excellent picture quality. Furthermore it is very easy to mount it on wall thanks to its unique design which requires 3 screw only, ideal for elevator, small shop or residential.

Specifications

Model	MR6822
Min. illumination/Low Light Mode (Colour)	Color : 0.02 Lux at F2.0 ; B/W : 0.005 Lux at F2.0 ; 0 Lux with IR LED O
Starting Temperature	-10°C – +50°C (14°F – 122°F)
Operating temperature	-40°C – +50°C (-40°F – 122°F)
Storage temperature	-25°C – +60°C (-13°F – 140°F)
Operating humidity	0% – 90% RH
Power Supply	DC12V ±10% / PoE (IEEE 802.3af compliant)
Power Consumption	DC12V, 4.5W / PoE, 5.5W
Lens	4mm
Iris	F2.0
Iris Control	Fixed IRIS
Angle of View	84.0° (H) 43.3° (V) 99.4° (D)
Peak wavelength	850nm
Beam Spread	60° , 90°
Max IR distance	30M
Pick Up Element	1/2.8" CMOS image sensor
Effective pixels	1945 (H) × 1097 (V) = 2,133,665 (pixels)
CE	Yes, EMI CLASS A
FCC	Yes, EMI CLASS A
IP Rating	IP67
CPU	Intel® Core™ i3 or higher grade
OS	Windows 7 or above
RAM	4GB or above, Dedicated Graphics Card

Web browser	Microsoft® Internet Explorer® 9 or above
Dimensions	Ø 73 × 62 (H) mm
Weight	230g
Casing Material	Aluminum alloy
Audio	One-way Audio, G.711 u-law / PCM / AAC, Built-in Microphone
Video Compression	H.264 main and high profile, Motion JPEG
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.264 and Motion JPEG, configurable frame rate and bandwidth
Number of streams	4
Video bitrate	128Kbps – 12Mbps; Frame rate and bit rate controllable on-the-fly; VBR / CBR / GOP supported; Fixed bitrate; Smart H.264
Encryption	Base64 HTTP encryption, HTTPS encryption
Authentication	Digest HTTP authentication, RTSP authentication, 802.1x, DDNS via HTTPS
Address Filter	IP address filter, MAC address filter
Access	Multiple user access levels with password protection
User accounts	10 simultaneous users
Multi IP address	Yes
Resolution	2MP(1920 × 1080), 1.3MP(1280 × 960), 1MP(1280 × 720), D1(720 × 480, 720 × 576), VGA(640 × 480), CIF(352 × 240)
Frame Rates	H.264 / MJPEG : up to 30 fps @ 1920 × 1080
Scanning System	Progressive Scan
Infrared Cut Filter	Auto / Day (Color) / Night (Mono) / Schedule
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Custom
Electrical Shutter	1/30(1/25)s – 1/30000s
Sense Up	Off / 1 Frame / 2 Frames

Sense Up+	Yes
Auto Gain Control	66 dB Variable Gain
S / N Ratio	More than 50dB (AGC off)
3D Noise Reduction	Off / 1 – 32 Selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode)
High Dynamic Range(HDR)	Up to 100dB (by HDR mode, 2 shutter line interleave)
Privacy Masking	Off / On (4 zones)
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip, Lens Distortion Correction
Mobile phone	Integrated to LILIN mobile app (LILIN Viewer), iPhone, iPad, Android support
Video Management	ONVIF Profile S, LILIN Navigator Enterprise 2.0, Third party VMS through LILIN HTTP API
Firmware	Firmware update via HTTP and IP Scan; Firmware available at website
IVS Basic 1.0	Motion Detection, Tampering Detection, Advanced Motion Detection, Traffic Light Detection, Tripwire Detection, Object Counting
Alarm event triggers	Motion / Tamper / Audio detection
Alarm event actions	FTP / SMTP / HTTP post / SAMBA / SNMP Trap / Push Service notification
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
Network Interface/Ethernet	10/100 Mbps Base-T, RJ-45
ePTZ & Digital Zoom	Yes, ROI (Region of Interest)
OSD	Text overlay for date, time, and camera name
CPU requirement	Embedded SoC ARM Cortex-A9, 600MHz, 256MB DDR3, 256MB flash memory
Network OS	Embedded Linux 3.10

Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, MQTT, QoS, SNMP, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SDDP, Bonjour, 802.1x, SSL/TLS
User accounts	10 simultaneous users
Video Display	LILIN Universal ActiveX & HTML5
