

MUTE SWITCH TECHNICAL DATA SHEET

DESCRIPTION

MS-2-REC is a switching device designed for audio monitoring and recording. The unit consists of two rocker switches, green and red. When illuminated, green represents live audio monitoring and red indicates that live audio is being recorded.

When the Green and Red Switches are in the off position, both the microphone and recording device are inactive and the two switches are not illuminated. The switches are manually turned ON and OFF. The Red Switch has an open contact (R1 and R2) and can be close to turn ON anything besides a recorder. The maximum capacity of the switch contacts are 9A @125Vac.

The Green and Red Switches are mounted to a double gang stainless steel face plate that fits into a 2-gang back box for flush or surface mounting to a wall or flat surface. The 2-gang box is not supplied.


A 12Vdc power supply for MS-2-REC unit is included.



MODEL MS-2REC

APPLICATION

- Interrogation/Interview Rooms
- Detention Centers
- Conference Rooms







- Rocker Switch for muting microphone audio
 Illuminates when audio is ON
- Fits in a standard single gang electrical box for flush or surface mounting

SPECIFICATIONS

Switch contact	9A @125Vac
Supply Voltage	12Vdc
Dimensions	2 ¾" W x 4 ½" H
Faceplate	303 Stainless Steel
Backbox	Single gang electrical box (not included)
Weight	2.5 oz
Shipping Weight	1 lb