

# 4MP 25X PTZ Advanced Analytic IP Camera with Smart Tracking and Included Wall Mount, NDAA Compliant

## **O4P25X2**

4.8-120mm 25x optical zoom lens, white housing



















#### **Features**

- Captures up to 4MP @ 30fps
- Up to 25x optical zoom
- Power with built in PoE++ support (IEEE 802.3bt) or included 24VDC power adaptor
- True Day/Night operation (IR cut filter)
- IR range up to 400ft (depending on scene reflection)
- True WDR Operation
- Micro SD card slot up to 256GB (card not included)
- Conformant with ONVIF Profile G/S/T

- Line Crossing, Video Blurring Detection
- People/Vehicle Detection
- Face Detection and Recognition\*
- Two-way audio support
- IP66 compliant, weather resistant
- Wall mount included
- 1 year warranty
- NDAA Compliant\*\*







Wall Mount Bracket

Camera Specifications		
Image Sensor	Progressive scan 1/2.7" CMOS, 4MP	
Maximum Resolution	2560 x 1440	
Minimum Illumination	0.01 lux @ F1.65, AGC ON; 0 lux with IR	
Field of View	Horizontal: $55^{\circ} \sim 2.4^{\circ}$ ; Vertical: $35^{\circ} \sim 1.4^{\circ}$ ; Diagonal: $61.5^{\circ} \sim 2.8^{\circ}$	
Image Settings	Flip, Mirror, Saturation, Brightness, Contrast, Sharpness	
Compensation	True WDR/BLC/HLC	
Day/Night	Smart IR with cut filter	
Electronic Shutter Speed	1s ~ 1/10000s	
DNR	3D DNR	
Angle Adjustment	Pan: 0° ~ 360°; Tilt -3°~90°	
Video Specifications		
Main Stream Resolution	4MP/3MP/1080P/720P (1~30fps)	
Sub Stream Resolution	1080P/1280x960/720P/D1/VGA/CIF (1~30fps)	
=1.10	/ / / /- / /	

Third Stream	D1/CIF/480x240 (1~30fps)
Compression	H.265, H.264, MJPEG
Multiple Streaming	3 streams

# Audio

**Audio Compression** G.711A/G.711U

#### Interfaces

Network	RJ45 jack
Power	AC/DC jack (24V)
Microphone Input	3.5mm
Audio Output	3.5mm
Card Slot	MicroSD, up to 256GB (card not included)
Alarm	1CH alarm input; 1CH alarm output
Reset	Yes
RS 485	No

### **Optional Accessories**







Ceiling Mount







### **Network Specifications**

Protocols	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE
DDNS Support	Speco DDNS (No fee)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication
User Access	Max. 16 simultaneous users (Actual number of users may vary depending on bandwidth)

#### **System Specifications**

System specifications	
PoE	PoE++ (IEEE 802.3bt)
Analytics	Line crossing, Intrusion (people/motor vehicle/non-motor vehicle classification), face detection.
Exception Detection	Scene change, video blur detection
Alarm Triggers	Motion, Sensor alarm, Analytics, SD card error
Image Settings	Watermark, IP address filtering, video mask, password protection
Action Modes	Preset/Cruise/Auto Scan/Random Scan
Client Specifications	

#### Client Specifications

Web Browser Support	Chrome, Edge, Safari, Firefox
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard® Client (iPhone® and Android™) , Speco Blue (iPhone® and Android™)

#### **Operating & Unit Specifications**

Power	PoE++ (IEEE 802.3bt), 24V AC/DC (power supply included)
Power Consumption	34W (max)
Operating Temperature	-22°F - 140°F
Operating Humidity	less than 95% RH (non-condensing)
Unit Dimensions	8.22" (Dia.) x 12.91" (H)
Unit Weight	8.31 lbs.
Certifications	IP66, FCC

<sup>\*</sup>with compatible Speco recorder

#### **Cameras Interfaces**































<sup>\*\*</sup>Products are in compliance with NDAA Section 889 Part B Guidelines