

Indoor Station

OEI-372S-H-W



Overview

OEI-372S-H-W indoor station is one of the terminals in the digital building intercom system, with functions of video intercom, security alarm, network camera monitoring, etc., providing a safe and comfortable living environment for residents. It can be widely used in building systems such as smart communities, villas, and office parks.

Features

- Durable ABS casing with a glass panel.
- 1024×600 HD touchscreen display.
- Batch configuration and transfer.
- Remote and one-touch unlocking of linked door stations.
- Network camera monitoring and security alarm.

Specifications

Model	OEI-372S-H-W
Hardware Specification	
Power Supply	DC12V±25%,IEEE802.3af, Standard PoE
Power Consumption	<10W
Screen	7-inch ultra-thin TFT LCD screen
Screen Resolution	Screen resolution 1024×600
Operation System	Linux
Audio Quality	Noise suppression, echo cancellation and AGC
Audio Input	1 built-in omnidirectional microphone
Audio Output	1 built-in speaker

Audio Compression Standard	MP3 G711
Audio Compression Bitrate	128Kbps
Interface	Power*1, network*1, WiFi*1, RS485*1, IO output*2, IO input*8, TF card slot*1
Network	100Mbps network port, supports IEEE802.3af PoE power supply, WIFI4、2.4GHZ
Weight	360g
Dimensions (L x W x H)	193mm×143mm×25mm
Operating Environment	-10°C to +55°C, 10% to 90%, non-condensing, indoor
Basic Business	
Protocol	UNV private protocol
Network protocol	TCP/IP, IPv4, HTTP, RTP, RTSP, NTP
Specification Index	
Capacity	200 ScreenShots 200 Zone AlarmsA total of 20 connected devices, including IPCs, entrance stations, NVRs (up to 2), and Doorbells
Linked Indoor Station Capacity	19 extensions

Ordering Info

Product Model	Description
OEI-372S-H-W	Wall Mounted 7-Inch Indoor Station(Touch Screen)

Accessories

OEP-SP11

Power Emboitement



Dimensions

