



1080P Day & Night Vari-Focal IP Box Camera



Features

- Full HD 2 megapixel CMOS image sensor
- 2MP H.265/HEVC and H.264/AVC high-performance video compression
- Simultaneous streaming of H.265 and H.264 encoded streams
- 3D noise reduction (MCTF)
- 2D WDR function
- HDR function up to 100dB
- Digital PTZ supported
- IVS supported
- Tampering / Audio / Alarm / Motion / Network lost detection event function
- Day & Night (IR cut removable)
- Built-in highly sensitive microphone
- 2-way audio supported
- Digital I/O : 1 in, 1 out
- ONVIF Profile S supported

Specifications

Model	P2G1022
Min. illumination/Low Light Mode (Colour)	Color : 0.03 Lux at F1.4 ; B/W : 0.002 Lux at F1.4
Starting Temperature	0°C – +50°C (32°F – 122°F)
Operating temperature	-20°C – +50°C (-4°F – 122°F)
Storage temperature	-25°C – +60°C (-13°F – 140°F)
Operating humidity	0% – 90% RH
Power Supply	DC12V ±10% / PoE (IEEE 802.3af compliant)
Power Consumption	DC12V, 5W / PoE, 6W
Pick Up Element	1/2.8" CMOS image sensor
Effective pixels	1945 (H) × 1097 (V) = 2,133,665 (pixels)
CE	Yes, EMI CLASS B
FCC	Yes, EMI CLASS B
CPU	Intel® Core™ i7 or higher grade
OS	Windows 7 or above
RAM	8GB or above, Dedicated Graphics Card
Web browser	Microsoft® Internet Explorer® 9 or above
Dimensions	70(W) × 50(H) × 110(D) mm
Weight	380g
Casing Material	Aluminum alloy
Audio Input / Output	Digital 1 input (TTL, +3 – 5VDC) / 1 Output (MOS Relay contact N.O., Load.max. 40VDC,450mW/300mA,450mW), Terminal block
Live Video Output	CVBS 1.0Vp-p, 75 ohm, RCA jack
Audio	Two-way Audio, G.711 u-law / PCM / AAC, SIP, Built-in Microphone
Alarm Input / output	Digital 1 input (TTL, +3 – 5VDC) / 1 Output (MOS Relay contact N.O., Load.max. 40VDC,450mW/300mA,450mW), Terminal block
Video Compression	H.265/HEVC main profile, H.264 main and high profile , Motion JPEG

Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.265 and H.264 and Motion JPEG, configurable frame rate and bandwidth
Number of streams	4
Video bitrate	128Kbps – 12Mbps; Frame rate and bit rate controllable on-the-fly; VBR / CBR / GOP supported, Fixed bitrate, Smart H.264/H.265
Encryption	Base64 HTTP encryption, HTTPS encryption
Authentication	Digest HTTP authentication, RTSP authentication, TLS, 802.1x, DDNS via HTTPS
Address Filter	IP address filter, MAC address filter
Access	Multiple user access levels with password protection
User accounts	10 simultaneous users
Multi IP address	Yes
Resolution	2MP(1920 × 1080), 1.3MP(1280 × 960), 1MP(1280 × 720), D1(720 × 480, 720 × 576), VGA(640 × 480), CIF(352 × 240)
Frame Rates	Normal mode 60Hz: 60 fps @ 1920 × 1080 50Hz: 50 fps @ 1920 × 1080 HDR mode 60Hz: 30 fps @ 1920 × 1080 50Hz: 25 fps @ 1920 × 1080
Scanning System	Progressive Scan
Infrared Cut Filter	Auto / Day (Color) / Night (Mono) / Schedule
White Balance	ATW-NARROW / ATW-WIDE / AWC(MANUAL)
Electrical Shutter	1/30(1/25)s – 1/30000s
Sense Up+	Off / 1 Frame / 2 Frames
Auto Gain Control	66 dB Variable Gain
S / N Ratio	More than 50dB (AGC off)
3D Noise Reduction	Off / 1 – 32 Selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode) Support Onvif
High Dynamic Range(HDR)	Up to 100dB (by HDR mode, 2 shutter line interleave)

Privacy Masking	Off / On (4 zones)
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip, Rotation
Mobile phone	Integrated to LILIN mobile app (LILIN Viewer), iPhone, iPad, Android support
Video Management	ONVIF Profile S / IVS events, LILIN Navigator Enterprise 2.0 support, Third party VMS through LILIN HTTP API
SD Card (recording)	Support (128GB) Micro SD/SDHC/SDXC card for circular recording (card is not included)
Maintenance	Firmware update via HTTP and IP Scan; Firmware available at web site
IVS (Intelligent Video Surveillance)	Motion Detection, Tampering Detection, Advanced Motion Detection, Tripwire, Traffic Light Detection, Object Counting
Alarm event triggers	FTP / SMTP / HTTP post / SD card / SAMBA / SMTP Trap
Alarm event actions	Motion / Tamper / Network lost detection / SmartEvent
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
Network Interface/Ethernet	10/100 Mbps Base-T, RJ-45
ePTZ & Digital Zoom	Yes, ROI (Region of Interest)
CPU.Memory	Embedded SoC ARM Cortex-A9, 816MHz, 512MB DDR3L, 256MB flash memory
OSD	Position configurable text overlay for date, time, camera ID, event status and watermark with customizable user demand data
Network OS	Windows 7 or above

Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, SIP, MQTT, QoS, SNMP V1/V2/V3, SNMP Trap and heart beat, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S , SDDP, Bonjour , 802.1x
Max number of online users	10 user accounts available
Video Display	LILIN Universal ActiveX , LILIN Java Applet
