

CAT6 UNSHIELDED KEYSTONE COUPLER, W/6 COLOR ID BARS, INLINE/SLIM STYLE, CAT6 UTP

PART#: \$45-3260B, \$45-3260B-25 \$45-3260W, \$45-3260W-25

PRODUCT SUMMARY

Keystone Cat6 UTP RJ45 couplers provide feed-through patching via any industry-standard patch panel, keystone wall plate, or surface mount box.

The snap-in RJ45 Cat6 connector jack is simple to install and provides a robust female to female in-line RJ45 Cat6 connector coupler.

FEATURES & BENEFITS

- Female to Female CAT6 UTP RJ45 Keystone Coupler
- 50µ Gold Plated
- Snap-in design / Slim Style
- Available in 10 packs
- RoHS Compliant
- ANSI/TIA 568.2-D
- ISO/IEC 11801 Class E
- Available in White S45-3260W and Black - S45-3260B

SPECIFICATIONS

| Electrical Specification | |
|---------------------------|----------------------------|
| | |
| Insulation Resistance | >= 500 MΩ |
| Dielectric Withstand Volt | 100VAC RMS 60Hz |
| Contact Resistance | <= 20 mΩ |
| Current Rating | 1.5A at 68°F |
| | |
| Mechanical Specifications | |
| | |
| Plug insertion Life | >=750 times plug in |
| Contact Force | 99.2g (3.5oz) FCC Plug |
| Plug Retention Force | 30lb (133n/13.3Kg) |
| Temperature Test | -40 to 150°F (-40 to 66°C) |
| Contact Plating | 50u" over contact area |
| Material | Polycarbonate, 94V0 rated |
| | |
| | |
| | |
| | |
| | |





