



SLA-F4780VA

5MP 4.7mm Lens

Key Features

- Discrete Pinhole type
- Compact Cube-type Design
- 4.72mm Fixed Focal Length
- 70° Horizontal Field of View (HFOV)
- 8m Cable for Flexible Installation
- Compatible with PNM-C20000QB

SLA-F4780VA

5MP 4.7mm Lens



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.09
	BW(1/30sec, 30IRE)	0.09

Lens

Focal Length (mm)		4.72
Max. Aperture Ratio (F number)	Wide	2.07
	Tele	2.07
Angular Field of View	Horizontal	70°
	Vertical	50°
	Diagonal	96°
Mount Type		RJ12 connected with main unit
Focus Control		Fixed

Environmental & Electrical

Operating Condition	Temperature	-10°C ~ +55°C (+14°F ~ +131°F)
	Humidity	0~95% RH
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	Less than 90% RH

Mechanical

Color	Black
Material	Plastic, Metal
Product Dimensions	30(W)x20.5(H)xD45mm(1.18x0.81x1.77"), Cable: 8m(26.2ft)
Product Weight	44.4g(0.1lb), Cable: 350g(0.77lb)

Certification & Standards

EMC	FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1

Certification & Standards

Environment	None, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78
--------------------	---

SLA-F4780VA

5MP 4.7mm Lens



CAD

Unit: mm [inch]

