



# SLA-T2880BA

2MP Network Bandit Barrier lens



## Key Features

- 2 Megapixel (1920 x 1080) resolution
- 2.8mm wide-angle lens
- H.265, H.264, MJPEG codec support, Multiple streaming
- 60fps@2MP (H.265 / H.264)
- WDR (120dB)
- Built-in Analytics
- SD / SDHC / SDXC memory slot (Maximum 256GB)
- Hallway View, WiseStream II support
- LDC, PoE / 12V DC, Bi-directional audio support
- Adjustable height and installation options for various installation types
- Includes XNB-6001 main unit & SLA-T2480 lens with 8m cable

# SLA-T2880BA

2MP Network Bandit Barrier lens



## Specifications

### Video

Imaging Device	1/2.8" 2M CMOS
Min. Illumination	Color: 0.045Lux(F2.0) BW: 0.045Lux(F2.0) * with PNM-9000QB, XNB-6002, PNM-C16000QB * without bandit barrier housing

### Lens

Focal Length (Zoom Ratio)	2.8mm fixed
Max. Aperture Ratio	F2.0
Angular Field of View	H: 108° / V: 63° / D: 122°
Min. Object Distance	0.5m(1.64ft)
Focus Control	Fixed
Mount Type	RJ12 connected with main unit

### Environmental & Electrical

Operating Temperature / Humidity	-10°C~+55°C(+14°F~+131°F) / 0~90% RH
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / 0~90% RH

### Mechanical

Color / Material	Housing: Black / Plastic, Aluminum Lens: Black / Plastic, Aluminum
Product Dimensions / Weight	Bandit Barrier: 66.5x46x175~737mm(2.6"x1.8"x6.9~29.0"), Main Unit: 131.1x28x86mm (5.16"x1.10"x3.39"), Cable: 8m(26.2ft) Bandit Barrier: 250~1,000g(0.55~2.205 lb), Camera Body: 245g(0.54 lb)