

**Electronic Technical Services Inc.** 

211 Conchas SE Albuquerque, NM 87123 PH 505-888-3923 FAX 505-888-3926 Website: www.etsnm.com

#### Description

Complete single zone, 2 microphone, audio surveillance system with built in speaker and headphone jack. Expands pickup coverage to 50 feet in all directions using 2 SM1 microphone signals mixed together. SMM2 mixer has volume controls for each microphone. The SM6-M2 can be used independently for monitoring live audio or with tape recorders and DVRs for recording and playback.

#### Kit Includes

- 2ea SM1 Pre-amplified microphone.
- SM3 Amplifier.
- SMM2 active microphone mixer.
- 12 VDC AC adapter.
- SM1 Mounting screws
- 3' Dual RCA Patch cable.
- 2ea. Warning label.

## **Options**

RM1, RM2, RM3 18" Rack mounts.

## **Wiring Requirements**

 Stranded 22-gauge, 2-conductor shielded cable with drain wire.
 Max. cable length: 1500'

### **SMM2 Mixer Specifications**

- Powered by SM3 base station.
- Level controls for each microphone.
- 3 position Euro-style connectors make cable terminations fast and clean.
- Power consumption 20ma@12Vdc.
- See SMM2 data sheet for more information.

# SM6-M2 Audio Surveillance Kit



## **SM1 Microphone Specifications**

- Omni-directional Electret element.
  25' range in all directions.
- Low noise MOSFET pre-amplifier.
- Line level, unbalanced output.
- Adjustable gain.
- Treble boost circuit. Selectable on/off.
  Enhances clarity of time lapse recordings.
- Limiter circuit. Selectable on/off.
- 3 position Euro-style connector makes cable termination fast and clean.
- Flush mountable. Can be mounted on a single gang electrical box.
- Power: 12 VDC @ 10mA.
- See SM1 data sheet for more information.

## **SM3 Amplifier Specifications**

- Standard RCA jacks for connection to tape recorders, DVRs, etc.
- 3 position Euro-style connector makes cable termination fast and clean.
- 1 Watt Power amplifier.
- 3" full range speaker.
- Tape monitor switch.
- 3.5mm Headphone jack.
- Power: 12 VDC @ 250mA.
- Reverse polarity protected and fused.
- Dimensions L 5.4 x W 4.1 x H 1.5
- See SM3 data sheet for more information.