



# SMT-2212



## Key Features

- 22" FHD Monitor, support up to 1920\*1080 60Hz (FHD)
- Brightness 250 cd/m<sup>2</sup> ( Typ ) , Contrast 2000:1(Min), 3000:1(Typ)
- Viewing Angle (H/V) : 178°/178°, Response Time : 6.5ms(Typical)
- Video Input : HDMI(1), VGA(1)
- Framelss design with monitor stand
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

# SMT-2212



## Specifications

### Display

Type	LED Monitor
Screen Size	22inch
Max. Resolution	1920x1080
Brightness	250 cd/m <sup>2</sup>
Contrast Ratio	3000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7M
Response Time	6.5ms
Panel Life	30,000 hours

### Interface

Video	Connectors	VGA(1), HDMI(1)
VGA	Connector	VGA
	Available Format	1920x1080@60Hz
HDMI	Connector	HDMI
	Available Format	1920x1080@60Hz

### On Screen Display

Functions	VESA™ DPMS Compatible
Language	English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic

### General

Electrical	Input Voltage	DC 12V 5A, Adapter included
	Power Consumption	30W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)

---

**General**

<b>Mechanical</b>	Dimensions with Stand (WxHxD)	491.9x186.7x371.4mm(19.4x7.4x14.6")
	Dimensions without Stand (WxHxD)	491.9x36.1x289.4mm(19.4x1.4x11.4")
	Weight	2.59Kg(5.7lb)
	Packing Dimension (WxHxD)	542*106*352mm(21.3x4.2x13.9")
	Packing Weight	3.13Kg(6.9lb)
	Cabinet Color	Black
	VESA Mounts Interface	100x100mm

# SMT-2212



CAD

Unit: mm [inch]

## SMT-2212

