



SPC-2010

PTZ, DVR Control Keyboard



Key Features

- Controls up to 255 PTZ cameras + DVR
- Superior system compatibility
- OSD Menu, 3D joystick control
- Built-in jog shuttle
- RS-485 and RS-422 compatibility
- 16 x 2 Character LCD display

SPC-2010

PTZ, DVR Control Keyboard



Specifications

Communication

Control Equipment		PTZ/DVR/Receiver
Interface		RS-485/422, RS-485/422
Interface Protocol	PTZ Camera	Samsung-T/E, Pelco-D/P, Panasonic, Vicon, AD, Honeywell, Bosch, Elmo, GE
	Zoom Camera	SCZ series
	DVR	SRD series(except SRD-480D)
	Receiver	Samsung-T(SRX-100B)
Baud Rate (RS-485/422)		2400 ~ 57,600bps

Operational

LCD Display	16 x 2 character LCD, English
Joystick	3 Axis twist zoom
Jog Shuttle	DVR Playback control

Environmental

Operating Temperature	0°C ~ 40°C (+32°F ~ +104°F)
Operating humidity	0 ~ 90%

Electrical

Input Voltage	12V DC
Power Consumption	1.1W

Mechanical

Dimensions (WxHxD)	334,1x171,1x105,2mm (13.15"x6.74"x4.14")
Weight	800g (1.76lb)