

HD Video Transceiver

TVIUTP

Features

- Send HD-TV signal up to 656' (200M) over UTP cable.
- BNC male to screw terminal for easy connection.
- Compact size allows mounting of multiple units behind multiplexers, Quads, DVRs, etc.
- Passive, No power required.
- Ideal for retrofits using existing UTP cable.
- Built in ESD, EFT (impulse noise), lightning (surge) and transient protection.
- Sold individually but used in pairs. Could be used in conjunction with another TVIUTP, or with the pigtail model **TVIUTPPT**.

**HD
TVI**



Sold Individually

Specifications

Video Input (BNC Connector).....	1
Video Input	1Vp-p, 75 Ohms
Cable	Twisted Pair CAT 5
Bandwidth.....	50Hz - 60MHz (-3dB)
Transmission Distance	HD-TV: 656' (200M)
RJ-45 Output	Terminal
ESD Protection	30 KV(Air) 15 KV (Contact) ; IEC 61000-4-2 compliant
EFT Protection.....	40A(5/50ns) ; IEC 61000-4-4 compliant
Lighting Protection.....	2A (8/20µs) ; IEC 61000-4-5 compliant
Surge Protection Attack Time	< 1 nS
Operating Temperature.....	32° F - 131° F,
Storage Temperature/Humidity....	-4° F - 185° F / up to 95%
Dimensions.....	0.6" (W) x 2" (H) x 0.6" (L)
Weight	0.64 oz.

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Also Available



TVIUTPPT
HD Video Transceiver
with Pigtail

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice
and without incurring any obligation. Spec Rev. 3/21/22