

**DESCRIPTION**

The Model Verifact® D USB is an omni-directional, low impedance, electret condenser microphone with a USB audio output. It can pick up normal sounds approximately 15 ft. away. Microphone assembly is mounted to the back of a single gang stainless steel faceplate that fits into a single gang electrical box. The Verifact® D USB is compatible with devices that accepts USB audio input. The unit can be flush or surface mounted to a wall or ceiling. Electrical box not included.



**APPLICATION**

When part of a Louroe Audio System, the Model A USB can be used in situations such as:

- Convenience Stores
- Fast Food Restaurants
- Booking Rooms
- Interrogation Rooms
- Day Care Centers
- Sleep Disorder Centers
- Therapy Labs
- Cashier Booths
- Gas Stations

**WIRING REQUIREMENTS**

Shielded USB type A - mini type B



**VERIFACT® D USB MICROPHONE**

**FEATURES**

- Sturdy vandal resistant front faceplate
- Microphone can pickup normal sounds 15 ft away
- Easily mounted to wall or ceiling surface
- Two position preamp gain setting: Normal and Low
- Fits into single gang electrical box (not included)
- Flush or surface mount to wall or ceiling

**SPECIFICATIONS**

■ Sensitivity	-45 dBV/Pa 1 Pa = 94 dB SPL
■ Frequency response	50 Hz to 15 kHz
■ Output	USB audio
■ Current drain	500 mA peak
■ Supply voltage	5 Vdc
■ Microphone housing	High impact anti-static ABS
■ Dimensions	4" dia x 1 1/2" H
■ Weight	3.5 oz
■ Shipping Weight	1 Lb

**IMPORTANT NOTICE**

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.



Federal Law References:  
 Federal Regulations, US Code, Title 18.  
 Crime and Criminal Procedure, Sec 2510.

