

TECHNICAL SPECIFICATION

57V 1U RACKMOUNT
POWER SUPPLY**POWER INPUT**

| | |
|-------------------------|---------------|
| Normal Input Voltage | 100 - 240V AC |
| Input Voltage/Frequency | 50/60Hz |
| Current | Max 5A |

POWER OUTPUT

| | |
|------------------------|--------------|
| Normal Output Voltage | 57V DC (x 6) |
| Maximum Output Current | 8.8A |

PHYSICAL/ENVIRONMENTAL

| | |
|----------------------------|--|
| Product Case Dimensions | L 442mm W 130mm H 44.5mm (without brackets) |
| Weight | 1860g, 4.1lb, |
| Operating Temperature | 0° ~ +40°C, [32°F~ +104°F], Full Load and natural convection |
| Storage Temperature | -10° ~ +70°C, [14°F~ +158°F], |
| Operating/Storage Humidity | 10 ~ 90% RH (non-cond) |
| Compliance | EN60950, EN55022A, CE, ROHS, FCC, UL, |
| Patch Cables | Supplied with 6 x 200mm DC Patch Cables |
| Input Power Cord 3-PIN-UK | 3- PIN C13 Power Cord with UK connector, (2 metre cord) |
| Input Power Cord 3-PIN-US | 3- PIN C13 Power Cord with US connector, (2 metre cord) |
| Input Power Cord 3-PIN-EU | 3- PIN C13 Power Cord with EU connector, (2 metre cord) |

LED DISPLAY AND INDICATORS

| | |
|-------------------|--|
| POWER LED - GREEN | Green > 100 W LED, Green > 200 W LED, Green > 300 W LED, |
| POWER LED - AMBER | Amber > 400 W LED |
| POWER LED - RED | Red Warning LED |

ASSOCIATED PRODUCTS

| | |
|-------------------|---|
| VHW-HWPS-B | HIGHWIRE Powerstar (POE over coax, BASE unit) |
| VHW-HWPS-B4 | HIGHWIRE Powerstar Base 4 (POE over coax, BASE unit) 4 port switch |
| VHW-HWPS-B8 | HIGHWIRE Powerstar Base 8 (POE over coax, BASE unit) 8 port switch |
| VLS-1P-BC | HIGHWIRE Longstar (long-range POE over coax, BASE unit) |
| VLS-1P-B | LONGSPAN Base Unit (long-range POE, powered via POE-in or VPSU-57V) |
| VCS-4P1, VCS-8P2, | CAMSWITCH 4 or 8 Plus (POE in or VPSU-57V) |
| VLS-1U | 1U 19" Rack mount plate for 24 x LONGSPAN or 24 x HIGHWIRE Longstar units |
| VRM-TRAY-BASE | 1U Rackmount tray and fascia x 4 VHW-HWPS-B8 or VCS-8P2 |

PRODUCT CODES

| | |
|----------------|---|
| VPSU-57V-1U-UK | 57V 1U Rackmount Power Supply with 6 microfit connectors. (UK Power cord) |
| VPSU-57V-1U-US | 57V 1U Rackmount Power Supply with 6 microfit connectors. (US Power cord) |
| VPSU-57V-1U-EU | 57V 1U Rackmount Power Supply with 6 microfit connectors. (EU Power cord) |

Surge Protection

All Veracity products have been independently tested to verify their resilience to the stringent immunity levels of international standards. Users should note that no electronic equipment can be guaranteed to be completely protected at levels beyond the defined standard ; therefore product warranty cannot include damage to products which has been caused by surges exceeding those of the standards specified, for example lightning strike activity.

It is the user's responsibility to implement relevant surge protection measures, as appropriate to the installation. This may include the fitting of additional surge protection devices where required.



veracity

Veracity HQ
Prestwick International Aerospace Park
4 Dow Road
Prestwick
UK
KA9 2TU
Tel +44 (0) 1292 264967
Fax +44 (0) 845 528 1081
www.veracityglobal.com
sales@veracityglobal.com

See www.veracityglobal.com website
for country specific contacts.