

VTC-CB5PN

Virtuoso Series Premium Starlight 5 MegaPixel Dual Voltage / PoE Network Box Camera with Triple Streaming and Motion Detection



KEY FEATURES

- 1/2.8" 5.69 Megapixel Sony® STARVIS Progressive Scan Starlight CMOS Sensor
- Image Size (Effective): 5 MegaPixel (2592 × 1944)
- Up to 30fps live view @ 5 MegaPixel
- H.265 / H.264 / MJPEG
- Video Streaming: Triple multi-streaming with simultaneous H.265, H.264, and MJPEG for integration with VITEK VMS and 3rd party apps/software
- Motion Detection via A.I. (Artificial Intelligence)
- Four A.I. Object Classifications for Human, Face, Cat, and Dog
- Privacy Mask, Defog, D-Zoom(~x16), Highlight Correction / Backlight Correction, Mirror/Flip, Sens-up (Slow shutter), Hue, Brightness, Contrast, Saturation, Sharpness, VerticalView(90°/270°)
- Day / Night Modes: ICR (Auto), Day, Night, External, Color D/N
- CS Mount Lens Support (Not Included)
- Remote Viewing with Chrome Firefox, Safari, Edge, IE
- Alarm In / Out
- External Audio In / Out*
- MicroSD Card Slot for Local Recording (up to 256GB)
- PoE / 12VDC / 24VAC Operation
- NDAA & TAA Compliant
- 3-Year Warranty

Virtuoso



*Lens Not included.



Sony STARVIS® is registered trademarks of an independently owned and operated company. This product has not been licensed or endorsed by the manufacturer of those products.

*Research local, state and federal laws regarding the implementation of audio surveillance.

VIRTUOSO SERIES 5 MEGAPIXEL PREMIUM COMPACT IP CAMERA WITH ONVIF S, MULTI-VENDOR DIRECT INTEGRATION AND MUCH MORE!




High Performance Virtuoso camera designs are produced for ease of installation, exceptionally high image quality, and long life. With an 5.69 MegaPixel "Starvis" Image Sensor, this compact "Box Style" camera achieves impeccably vibrant image quality even in extremely low light conditions. Digital Wide Dynamic Range cuts glare in difficult lighting environments such as casino halls, warehouses, and dimly lit foyers. Dual Voltage 12/24V operation (plus PoE) reduces the challenge of cable distance constraints.

RELATED PRODUCTS



Pair with one of several VITEK Network or Digital Recorders offering a Myriad of Advanced Analytic Functions and Applications. See www.vitekccv.com for More!

Firmware and Features may be upgraded periodically – Please contact your VITEK Representative for complete information on updates and downloads.



VTC-CB5PN

Virtuoso Series Premium Starlight 5 MegaPixel Dual Voltage / PoE Network Box Camera with Triple Streaming and Motion Detection



FEATURES

LENS DISTORTION CORRECTION:



LDC OFF

The design of CCTV lenses can cause optical distortions.



LDC ON

Virtuoso LDC corrects distortions with A.I. Powered Dewarping!

VIRTUOSO SERIES DIGITAL WDR:



WITHOUT WDR

The bright background prevents proper exposure of the subject.



WITH VIRTUOSO D-WDR

The entire frame is clearly visible & exposed with High Quality Digital WDR!

STARLIGHT:



STARLIGHT DAYLIGHT IMAGE


Uses an RGB Bayer Array CMOS for color accurate daylight images.



STARLIGHT NIGHT IMAGE

Starlight enables ultra low light performance at night!

HARDWARE & REAR INPUTS



DETAILED SPECIFICATIONS

| | |
|------------------------------|--|
| Imaging Sensor | 1/2.8" Sony 5.69 Mega pixel STARVIS CMOS Sensor |
| Effective Pixels | 2592(H) × 1944(V) approx. 5 Megapixel |
| Sensitivity | B/W 0.008 Lux |
| Scanning mode | Progressive Scan |
| S/N Ratio | 50dB |
| Video Compression | H.265 Main profile, H.264(High, Main, Baseline profile) MJPEG |
| Video Streaming | Simultaneously H.265, H.264 & MJPEG (Multi streaming), Independent Frame Rate and Bandwidth Control, VBR/CBR |
| Video Resolution | 4:3 - 2592×1944, 2560×1920, 2048×1536, 1920×1440, 1600×1200, 1280×960, 640×480, 480×360 16:9 - 2560×1440, 1920×1080, 1600×900, 1280×720, 640×360 |
| Video Frame Rate | Up to 30fps |
| Functions | Motion Detection, Privacy Mask, Defog, D-Zoom (~x16), Highlight Correction, Backlight Correction, Mirror/Flip, Sens-up(Slow shutter), Hue, Brightness, Contrast, Saturation, Sharpness |
| Lens | CS Mount Lens Support (Option: C-mount Adaptor) |
| Day & Night Mode | ICR by Auto, Day, Night, External, Color D/N |
| Auto Exposure | Automatic (Priority: Frame rate/Low noise), Manual |
| Shutter Speed Control | Automatic / Manual: Min. 1/30 sec ~ Max. 1/10,000 sec |
| Gain Control | Automatic: ~ Max. 54dB / Manual: ~ Max. 54dB (default:1.2dB) |
| Auto White Balance | ATW-Indoor/Outdoor, Shade, Clear Sky, Fluorescent Light, Light Bulb, Flame, Manual |
| WDR | D-WDR (Digital Wide Dynamic Range) |
| DNR | XD-NR (3D-NR / 2D-NR) |
| Audio | 2-way Audio* |
| Alarm | Alarm Input / Output |
| Protocol | TCP / IP, UDP, IP v4 / v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf |
| Security | Multi-User Authority, IP Filtering, HTTPS, Video Stream, Export / Import |
| FTP Uploading | MJPEG Still Image |
| Login Authority | Administrator, Operator, Guest |
| Network Time Sync. | Synchronize Computer/NTP Server, Manual |
| Software Reset | Reset, Factory Default |
| Remote Upgrade | Using Web Browser |
| Client Software | Built-In Web, ONVIF Compatible 3rd Party VMS |
| SDK Support | API, ONVIF Profile S Compliant |
| Local Storage | Card Slot for Micro SD Memory Card (256GB) |
| Power Source | PoE (IEEE Std. 802.3af), AC24V/DC12V |
| Power Protection | Circuit protection against faulty connection in power polarity. Isolated power supply protects against ground loop problem |
| Housing | Aluminum Cast |
| Operating Temp. | (-22°F ~ 122°F) -30°C ~ +50 °C (Humidity: 20%RH ~ 80%RH) |
| Dimensions W × H × L | 2.91" × 2.83" × 3.50" (74mm × 72mm × 89mm) |
| Weight (Net) | .66lbs / 10.58oz / 300g |

*Research local, state and federal laws regarding the implementation of audio surveillance.
Sony STARVIS® is a registered trademark of an independently owned and operated company. This product has not been licensed or endorsed by Sony®.