


VTC-THT2RMS

Transcendent 2.0 Megapixel Indoor/Outdoor 4-in-1 HD-over-Coax Turret Camera with a Motorized Varifocal Lens



Also Available in Charcoal Gray (VTC-THT2RMSB)



CABLE CONNECTIONS
12VDC Power Output, CVBS Output, Signal Switch



HD
ANALOG COAX



TRANSCENDENT



HD OVER COAX



MULTI FORMAT



2 MEGAPIXEL



MATRIX IR LED



MOTORIZED VARIFOCAL LENS



STARLIGHT

FEATURES:

- 1/2.8" 2.0 Megapixel Progressive Scan CMOS Sensor
- Advanced Starlight Technology Offers Dramatically Higher Sensitivity to Light Producing Color Images in Very Dark & Night Scenes
- 4-in-1 Multi-format: HD-TVI / AHD / CVI / CVBS (Selectable) Video Output
- 2.8-12mm Motorized Varifocal Lens
- 2 Matrix Style IRs with up to 165' IR Range
- True Wide Dynamic Range (WDR)
- True Mechanical Day/Night function by ICR
- XD-DNR (3D / 2D) Noise Reduction
- IP67 Weather Resistance
- Supports Control over COAX
- Over 1500' HD Video Transmission (Depending on cable characteristics and integrity)
- Available in Ivory or Charcoal Gray
- Optional Junction Boxes (VT-TJB01, VT-TJB021), Wall Mount (VT-TWMT-4) and Pendant Mounts (VT-TPDM-2 [use w/ VT-TJB01], VT-TPDM-3 [use w/ VT-TJB021])
- 12VDC Operation
- NDAA Compliant
- 3 Year Warranty

Transcendent Series High Definition 1080P HD-TVI, AHD, CVI, and CVBS 4-IN-1 Cameras offer unprecedented performance and value.

These simple, easy to install, attractively styled, analog HD Cameras transmit over your existing Coaxial cable at distances up to 1500'.

5-in-1 Digital Video Recorders Supporting HD-TVI / AHD / CVI / 960H Cameras



Transcendent Series 4, 8, 16 or 32 Channel 5-In-1 Digital Video Recorders Support HD-TVI / AHD / CVI / 960H Cameras as well as IP Cameras.



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

**An Eye On
Innovation**

Specifications

Image Sensor	1/2.8" 2.0 Megapixel Progressive Scan CMOS Sensor with Advanced Starlight Technology
Signal System	PAL/NTSC
Effective Pixels	1920 x 1080
Resolution	HD-TVI / AHD / CVI: 2.0 MegaPixel / CVBS: 960H
Video Output	HD-TVI / AHD / CVI / CVBS (Selectable)
Lens	2.8-12mm Motorized Varifocal
Day/Night	True Day/Night by ICR
Min. Illumination	Color: 0.001 lux@F1.2, AGC ON / B/W: 0 lux (with IR ON)
IR LEDs	2 Matrix IRs
IR Distance	165'
S/N Ratio	≥52dB (AGC Off)
WDR	True WDR
Defog	YES
Digital Noise Reduction (DNR)	XD-DNR (3D-DNR / 2D-DNR)
White Balance	Auto (AWB)
BLC	YES
Up the COAX Control (COC)	YES
Transmission Distance	Up to 1500' (Depending on cable characteristics & integrity)
Power Input	12VDC
Power Consumption (12VDC)	IR Off: 120mA / IR ON: 360mA
Weather Resistance	IP67
Operation Conditions	-4 ~ 122 / 10% ~ 90% Humidity
Weight	22.57oz / 1.41lb / 640g
Dimensions	4.34" x 5.15" (131 x 110mm)) H x Dia
NDAA Compliant	YES



TRANSCENDENT



HD OVER
COAX



MULTI
FORMAT



2 MEGAPIXEL



MATRIX IR LED
ILLUMINATION



MOTORIZED
VARIFOCAL



STARLIGHT



VT-TJB01
Optional Junction
Box for use with
Select
Transcendent
Turret and
Bullet Cameras



VT-TJB021
Optional Junction
Box for use with
Transcendent
Motorized Turrets
and Domes



VT-TWMT-4
Optional Wall
Mount for use
with Motorized
Transcendent
Turrets



VT-TPDM-2
Mount Post Adapter -
requires
VT-TJB01



VT-TPDM-3
Pendant Mount Post
Adapter - requires
VT-TJB021



This Product Complies with the Regulations of the
John McCain National Defense Authorization Act of 2019