

# VTC-TNT6FEA-2

Transcendent Series 6 MegaPixel Fixed Lens IP WDR Turret Camera with Programmable Analytics



## KEY FEATURES

- 1/2.5" 6.0 MegaPixel CMOS Image Sensor
- Up to 20fps@6MP (3200 × 1800), Up to 30fps@4MP (2688 × 1520)
- 2.8mm Fixed Iris Lens
- Matrix IR / White Light (up to 100' Range)
- True Wide Dynamic Range (120dB)
- True Mechanical Day/Night function by ICR
- XD-DNR (3D & 2D-DNR) Noise Reduction
- Region Intrusion Detection, Object Abandoned / Missing, Scene Change Detection, Line Crossing, Video Blur, Video Color Cast Detection
- H.265+ / H.265 / H.264+ / H.264 / MJPEG
- MicroSD Card Slot for Local Recording (Up to 256GB)
- 1 Ch. Audio In + Built-in Mic\*
- Remote Viewing via VMS, Internet Explorer (Plug-in Req'd), Edge in IE Mode, and iOS & Android Apps
- ONVIF Compliant
- IP67 Weather Resistance
- Optional Wall Mount (VT-TWMT-3), Junction Boxes (VT-TJB01, VT-TJB08), and Pendant Mount VT-TPDM-2 [reqs. VT-TJB01] Available [See Additional Mounting Options Below]
- 12VDC & PoE (Power over Ethernet) Operation
- 3-Year Warranty



\*Also available in Charcoal, VTC-TNT6FEAB-2



**CABLE CONNECTIONS**  
Ethernet (PoE), 12VDC Input, Audio In\*



**MICRO SD CARD SLOT**  
Supporting up to 256GB MicroSD Cards



## TRANSCENDENT SERIES NDAACOMPLIANT IP CAMERAS WITH PROGRAMMABLE ANALYTICS!

Transcendent Series NDAA Compliant High Definition 6 Megapixel IP Network Cameras offer unprecedented performance and value. These simple, easy to install, attractively styled, IP Network Cameras transmit over remote viewing via VMS, Web Browser, and iOS & Android Apps. These models also feature enhanced night vision using White Light emitter.

## TRANSCENDENT ANALYTICS!



**OBJECT TRACKING**  
Track Objects Removed from or Abandoned in Secure Areas



**AREA**  
Fully Programmable Regional Intrusion Detection



**LINE CROSSING**  
Track People or Vehicles Entering / Exiting Designated Areas

## RELATED PRODUCTS & ACCESSORIES



Pair with one of several VITEK Transcendent Series Network or Digital Recorders offering a Myriad of Advanced Analytic Functions and Applications. See [www.vitekccctv.com](http://www.vitekccctv.com) for More!

Firmware and Features may be upgraded periodically – Please contact your VITEK Representative for complete information on updates and downloads.

**VT-TWM04X**  
Wall Mount Bracket for Transcendent Fixed Turret Cameras

**VT-TJB08**  
Optional Junction box for Cable Management

**VT-TJB01**  
Optional Junction box for Cable Management

**VT-TPDM2**  
Pendant Mount - reqs. VT-TJB01

**VT-TWMT3**  
Optional Wall Mount

**VT-TPLMT**  
Universal Pole Mount Adapter - reqs. VT-TJB08 / VT-TJB01

**VT-TCNMT**  
Universal Corner Mount Adapter - reqs. VT-TJB08 / VT-TJB01



### BREAKDOWN OF MODEL NUMBERS EXAMPLE: VTC-TNT6FEA-2

[VTC] [T] [N] [T] [6] [F] [E] [A] [2]  
VITEK TRANSCENDENT Network Turret 6MP Fixed Entry Second Level Iteration 2.8mm Camera

An Eye On Innovation



[www.vitekccctv.com](http://www.vitekccctv.com)



## DETAILED SPECIFICATIONS

<b>Image Sensor</b>	1/2.5" CMOS
<b>Image Size</b>	3200 × 1800
<b>Electronic Shutter</b>	1/4s ~ 1/100000s
<b>Iris Type</b>	Fixed Iris
<b>Min. Illumination</b>	0.008 lux @F1.6, AGC ON; 0 lux with illumination on
<b>Lens</b>	2.8mm@F1.6, Horizontal FoV: 104°, Vertical FoV:55°, Diagonal FoV:128°
<b>Focus</b>	Fixed
<b>Day &amp; Night</b>	ICR
<b>Wide Dynamic Range</b>	120dB
<b>BLC</b>	Yes - Backlight Control
<b>HLC</b>	Yes - Highlight Control
<b>Digital Noise Reduction</b>	Yes
<b>S/N Ratio</b>	50dB
<b>Angle Adjustment</b>	Pan: 0°~360°, Tilt:0°~90°, Rotation: 0°~360°
<b>Video Compression</b>	Main stream: H.265+ / H.265 / H.264+ / H.264, Sub /Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
<b>H.265 Standard</b>	Main Profile @ Leve4.1 High Tier
<b>Resolution</b>	6MP (3200 × 1800), 4MP (2688 × 1520), 1080P (1920 × 1080), 720P (1280 × 720), D1, VGA (640 × 480), 480 × 240, CIF
<b>Main Stream</b>	60Hz: 6MP(1~20fps) /4MP/1080P (1~30fps) 50Hz: 6MP(1~20fps) /4MP/1080P (1~25fps)
<b>Sub Stream</b>	720P/D1/VGA/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
<b>Third Stream</b>	D1/480 × 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
<b>Bit Rate</b>	64 Kbps ~8Mbps
<b>Bit Rate Type</b>	VBR / CBR
<b>Image Settings</b>	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
<b>Audio Compression</b>	G711A/U
<b>ROI</b>	Each ROI to be configured separately
<b>Network</b>	RJ45
<b>CVBS Video Out</b>	No

<b>Audio</b>	1CH Audio Input, 1CH Built-in MIC*
<b>Storage</b>	Built-in micro SD card slot (up to 256GB) + Network Remote Storage
<b>Reset</b>	Yes
<b>Remote Monitoring</b>	Web browser / Transcendent NVR / VMS / Mobile App
<b>Web Browser</b>	Chrome 89.0+ / Edge 89.0+ / Firefox 87.0+ / Safari 14.0+
<b>Online Connection</b>	Support simultaneous monitoring for up to 6 users, Support multi-stream real time transmission
<b>Network Protocol</b>	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, HTTP POST, P2P, QoS
<b>Interface Protocol</b>	ONVIF
<b>Smart Alarm</b>	Motion detection, SMD, SD card error, SD card full, IP address conflict, network disconnection, video exception
<b>Programmable Analytics</b>	Line crossing / Region Intrusion Detection (by human / vehicle classification), Object Abandoned / Missing, Scene Change Detection, Video Blur, Video Color Cast Detection
<b>More Features</b>	Watermark, IP address filtering, video mask, heartbeat, ANR, cloud upgrade, smart supplement light, corridor pattern
<b>PoE</b>	Yes (IEEE802.3af)
<b>Supplement Light Range</b>	IR range: up to 100', White light range: up to 100'
<b>Ingress Protection</b>	IP67
<b>Security</b>	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP
<b>D.O.R.I.</b>	Detect: 218ft (66m) Observe: 87ft (27m) Recognize: 44ft (13m) Identify: 23ft (7m)
<b>Power Supply</b>	DC12V/PoE
<b>Power Consumption</b>	≤6.5W
<b>Operating Conditions</b>	-22°F~140°F (-30°C ~ 60°C), Humidity: less than 95 % (non-condensing)
<b>Dimensions Dia × H</b>	3.77 × 4.25" (95.7 × 108mm)
<b>Weight</b>	1.17lbs / 18.70oz / 0.53kg (NET) 1.37lb / 21.87oz / 0.62kg (SHIPPING)
<b>Installation</b>	Ceiling mounting, Wall mounting
<b>Certificates</b>	CE, FCC

\*Please research local, state and federal laws regarding the implementation of audio surveillance.