

# VTD-TND4MEA

Transcendent 4 MegaPixel Motorized AF IP Dome Camera with Programmable Analytics



## KEY FEATURES

- 1/3" 4.0 MegaPixel CMOS Image Sensor
- Up to 30fps@4MP (2560x1440)
- 2.8~12mm Motorized Varifocal Lens
- Matrix IR (up to 165' IR Range)
- True Wide Dynamic Range (120dB)
- True Mechanical Day/Night function by ICR
- XD-DNR (3D & 2D-DNR) Noise Reduction
- Programmable Analytics: Line crossing / Region Intrusion Detection (by Human / Vehicle Classification), Object Abandoned / Missing, Scene Change Detection, Video Blur, Video Color Cast Detection
- H.265+ / H.265 / H.264+ / H.264 / MJPEG
- MicroSD Card Slot for Local Recording (Up to 256GB)
- 1 Ch. Audio In + Built-in Mic\*
- Remote Viewing via VMS, Web Browser, and iOS & Android Apps
- ONVIF Compliant
- IP67 Weather Resistance + IK10 Impact Resistance
- Optional J-Boxes and Various Mounting Options Available - see below
- 12VDC & PoE (Power over Ethernet) Operation
- 3-Year Warranty



\*Also available in Charcoal, VTD-TND4MEAB

**MICRO SD CARD SLOT**  
Supporting up to 256GB  
MicroSD Cards



**CABLE CONNECTIONS**  
Ethernet (PoE), 12VDC  
Input, Audio In\*



TRANSCENDENT

NETWORK

INTEGRATED AUDIO

4 MEGAPIXEL

MATRIX IR ILLUMINATION

MOTORIZED VARIFOCAL LENS

PROGRAMMABLE ANALYTICS




## TRANSCENDENT ANALYTICS!



**OBJECT TRACKING**  
Track Objects Removed from or Abandoned in Secure Areas




**AREA**  
Fully Programmable Regional Intrusion Detection



**LINE CROSSING**  
Track People or Vehicles Entering / Exiting Designated Areas

## TRANSCENDENT ADVANCED IP CAMERA WITH PROGRAMMABLE ANALYTICS!

Transcendent Series NDAA Compliant High Definition 4 Megapixel IP Network Cameras offer unprecedented performance and value. These simple, easy to install, attractively styled, IP Network Cameras transmit over remote viewing via VMS, Web Browser, and iOS & Android Apps.



## RELATED PRODUCTS & ACCESSORIES



Pair with one of several VITEK Transcendent Series Network or Digital Recorders offering a Myriad of Advanced Analytic Functions and Applications. See [www.vitekccctv.com](http://www.vitekccctv.com) for More!

Firmware and Features may be upgraded periodically – Please contact your VITEK Representative for complete information on updates and downloads.



**VT-TJB010**  
Optional Junction box for Cable Management



**VT-TPDMT-A2**  
Pendant Mount (VT-TJB010 Req)



**VT-TWMT-A2**  
Wall Mount (VT-TJB010 Req)



**VT-TWM03X**  
Changeable Plate Universal Wall Mount



**VT-TFMT-L2**  
In-ceiling Semi-flush Mount



**VT-TPLMT**  
Universal Pole Mount Adapter (VT-TWM03X or VT-TWMT-A2 + VT-TJB010 Req)



**VT-TCNMT**  
Universal Corner Mount Adapter (VT-TWM03X or VT-TWMT-A2 + VT-TJB010 Req)



[www.vitekccctv.com](http://www.vitekccctv.com)

\*Please research local, state and federal laws regarding the implementation of audio surveillance.



## DETAILED SPECIFICATIONS

<b>Image Sensor</b>	1/3" CMOS
<b>Image Size</b>	2560×1440
<b>Electronic Shutter</b>	1/1s ~ 1/100000s
<b>Lens</b>	2.8~12mm Motorized Varifocal
<b>Min. Illumination</b>	0.004 lux @F1.4, AGC On, 0 lux with illumination on
<b>Field of View</b>	Horizontal 92°~31°, Vertical: 48°~17.2°, Diagonal: 112°~35.6°
<b>Focus</b>	Motorized AutoFocus
<b>Supplemental Light Range</b>	Matrix IR Range: up to 165'
<b>Day &amp; Night</b>	ICR
<b>Wide Dynamic Range</b>	120dB
<b>BLC</b>	Yes - Backlight Control
<b>HLC</b>	Yes - Highlight Control
<b>Digital Noise Reduction</b>	Yes - DNR
<b>S/N Ratio</b>	≥50dB
<b>Angle Adjustment</b>	Pan: 0°~345°, Tilt:0°~80°, Rotation: 0°~345°
<b>Video Compression</b>	Main stream: H.265+ / H.265 / H.264+ / H.264, Sub /Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
<b>H.265 Standard</b>	Main Profile@Leve4.1 High Tier
<b>Resolution</b>	4MP (2560×1440), 3MP (2304×1296), 1080P (1920×1080), 720P (1280×720), D1, VGA (640×480), CIF (480×240)
<b>Main Stream</b>	60Hz: 4MP/1080P (1~30fps) 50Hz: 4MP/1080P (1~25fps)
<b>Sub Stream</b>	720P/D1/VGA/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
<b>Third Stream</b>	D1/480× 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
<b>Bit Rate</b>	64 Kbps ~6Mbps
<b>Bit Rate Type</b>	VBR / CBR
<b>Image Settings</b>	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
<b>Audio Compression</b>	G711A/U
<b>ROI</b>	Each ROI to be configured separately
<b>Network</b>	RJ45
<b>CVBS Video Out</b>	No
<b>Audio</b>	1CH audio input, 1CH built-in MIC*

## DETAILED SPECIFICATIONS

<b>Storage</b>	Built-in micro SD card slot (up to 256GB)
<b>Reset</b>	Yes
<b>Remote Monitoring</b>	Web browser / Transcendent NVR / VMS / Mobile App
<b>Web Browser</b>	Chrome 89.0+ / Edge 89.0+ / Firefox 87.0+ / Safari 14.0+
<b>Online Connection</b>	Support simultaneous monitoring for up to 3 users, Support multi-stream real time transmission
<b>Network Protocol</b>	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, HTTP POST, P2P, QoS
<b>Interface Protocol</b>	ONVIF
<b>Smart Alarm</b>	Motion Detection, SMD, SD Card Error, SD Card Full, IP Address Conflict, Network Disconnection, Video Exception
<b>Programmable Analytics</b>	Line crossing / Region Intrusion Detection (by human / vehicle classification), Object Abandoned / Missing, Scene Change Detection, Video Blur, Video Color Cast Detection
<b>More Features</b>	Watermark, IP address filtering, video mask, heartbeat, ANR, cloud upgrade, smart supplement light, corridor pattern
<b>PoE</b>	Yes (IEEE802.3af)
<b>Ingress / Impact</b>	IP67 Weather Resistance + IK10 Impact
<b>Security</b>	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP
<b>D.O.R.I.</b>	2.8~12mm(W) Detect: 210ft (64m) Observe: 84ft (26m) Recognize: 42ft (13m) Identify: 20ft (6m) 2.8~12mm(T) Detect: 619ft (189m) Observe: 247ft (75m) Recognize: 124ft (38m) Identify: 62ft (19m)
<b>Power Supply</b>	DC12V/PoE
<b>Power Consumption</b>	≤7.5W
<b>Operating Conditions</b>	-22°F~140°F (-30°C~60°C), Humidity: less than 95 % (non-condensing)
<b>Dimensions (Dia x H)</b>	5.55" x 3.95" (141 x 100mm)
<b>Weight</b>	1.94lbs / 31.04oz / 0.88kg
<b>Installation</b>	Ceiling mounting, wall mounting - see additional optional mounting options on page 1
<b>Certificate</b>	CE, FCC
<b>Environmental Protection</b>	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

\*Please research local, state and federal laws regarding the implementation of audio surveillance.

**BREAKDOWN OF MODEL NUMBERS EXAMPLE: VTC-TND4MEA**  
**[VTC]** VITEK **[T]** TRANSCENDENT **[N]** Network **[D]** Dome **[4]** 4MP **[M]** Motorized **[E]** Entry **[A]** Second  
 Camera Level Iteration

