

VTC-THB2RFE-2

Transcendent Series 2 MegaPixel Indoor/Outdoor
4-in-1 HDA Fixed Bullet Camera




VITEKCCTV.COM
(888) VITEK-70



KEY FEATURES

- 1/2.9" 2.1 MegaPixel Progressive Scan CMOS image sensor
- High Definition Analog (HDA): HD-TVI / AHD / HD-CVI: 1080p/720p (2.1 MegaPixel) / CVBS: 960H Video Output
- 2.8mm Fixed Iris Lens
- 1 Matrix IR with up to 100' IR Range
- Digital Wide Dynamic Range (D-WDR)
- True Mechanical Day/Night function by ICR
- XD-DNR Noise Reduction
- IP67 Weather Resistance
- Supports Up The COAX Control
- Over 1500' HD Video Transmission (Depending on cable characteristics and integrity)
- 12VDC Operation
- Included Wall / Ceiling Mount & Optional Junction Box Mounts Available (VT-TJB07, VT-TJB08)
- 3 Year Warranty

ACCESSORIES



VT-TJB07
Optional Junction
Box for Use with
Select Transcendent
Bullet Cameras



VT-TJB08
Optional Junction
Box for Use with
Select Transcendent
Bullet
and Turret Cameras



VT-TR4VPK
Video and
Power Balun
Transmitter / Receiver
Pair for
HD-TVI /
AHD /
CVI for
Distances
Up to 1000'

VT-TR4K
Passive
Video Balun
Transmitter /
Receiver Pair
for HD-TVI /
AHD / CVI for
Distances Up
to 1440'

RECORDERS



Pair with VITEK Transcendent
Series 5-in-1 Digital Video Recorders
Supporting HD-TVI / AHD / CVI / IP /
960H Cameras!

SPECIFICATIONS

Image Sensor	1.29" 2.1 MegaPixel Progressive Scan CMOS Sensor
Signal System	NTSC/PAL
Effective Pixels	1920 x 1080
Resolution	HD-TVI / CVI / AHD: 1080p/720p (2.1 MegaPixel) / CVBS: 960H
Video Output	HD-TVI / CVI / AHD & CVBS (Selectable)
Lens	2.8mm - Fixed
Day/Night	True Day/Night by ICR
Min. Illumination	Color: 0.01 lux@F1.2, AGC ON / B/W: 0 lux (with IR ON)
IR LEDs	1 Matrix
IR Distance	Up to 100'
Dynamic (Smart) IR	YES
S/N Ratio	≥52 dB (AGC Off)
Wide Dynamic Range	D-WDR (Digital Wide Dynamic Range)
Digital Noise Reduction	3D-DNR
Auto White Balance	YES (AWB)
BLC	YES
Control over COAX	YES (COC)
Transmission Distance	Up to 1500' (Depending on Cable Characteristics and Integrity)
Power Input	12VDC
Power Consumption	IR Off: < 1W / IR On: < 3W
Weather Resistance	IP67
Operation Conditions	-4° ~ 122° / 10% ~ 90% Humidity
Dimensions	6.59" × 2.93" 2.93" (167.5mm × 74.5mm × 74.5mm)
Weight	15.52oz / .97lb / 440g

