



VZ-PVM-I4W3N ADVANTAGES

- 32" Mega Pixel IP Full HD 1080p Resolution
- Onvif Profile S Compliant
- Protective Glass / IPS Panel for Wider Viewing Angle - 178° / 178°
- Camera Motion Sensor & Time Interval Based Source Switching
- Auto Power / Source Recovery
- Built-in 2 Mega Pixel Camera / 600 TV Line - Analog Video Resolution
- PIP / PBP
- BNC(NTSC/PAL), VGA, HDMI, RJ-45, Audio, DC 12V Out
- 3D Comb-filter, De-interlace
- "A" Commercial Grade LED
- Supports Dual Voltage (110V AC and 24V DC)
- 3-Year Warranty



MODEL #		VZ-PVM-I4W3N	
DISPLAY			
Screen Size	32"		
Max. Resolution	1920 x 1080 @60Hz		
Pixel Pitch	0.36375mm x 0.36375mm		
Brightness	300cd/m ² (Typical)		
Contrast Ratio	1200:1		
Aspect Ratio	16 : 9		
Viewing Angle (H/V)	178° / 178°		
Display Color	16.7 Million		
Response Time	< 8 ms		
Video System	NTSC / PAL		
INTERFACE			
AV (Composite) In	1		
Camera (CVBS) Out	1		
HDMI In / VGA In (15Pin D-Sub)	1 / 1		
Audio In / Out	1 / 1		
Ethernet 10 / 100	1		
DC12V Out (Camera Use)	1		
SPECIAL FEATURES			
Multi Display Function	PIP / PBP		
Filter Type	3D Comb-filter / De-Interlace		
Multi-lingual Language	English, Spanish, French, Russian, Portuguese		
AUDIO			
Built in Speaker	5W x 2		
DIMENSIONS & WEIGHT			
Outline Dimension (W x H x D)	28.86" x 20.01" x 2.17"		
	733.2mm x 508.3mm x 55.3mm		
Net Weight / Gross Weight	33.06 lbs (15.00 kg) / 39.68 lbs (18.0 kg)		
MOUNT			
VESA	200mm x 200mm / M6 x L8 Screws		
GENERAL			
Transmitter - IR Remote Control	YES		
Power	Electrical Ratings	AC 110~240V (50/60Hz) 24V DC / 4A	
	Consumption	≤ 50 W	
Warranty	Parts/ Labor	3 Year / 3 Year	
Operating Temperature	32 - 104°F / 0 - 40°C		
Regulation	cUL, FCC(A), CE		
Compatible Mounts	Wall	VZ-WM50, VZ-AM02	
	Ceiling	VZ-CMKIT-01, VZ-CMKIT-02	

CAMERA	
Camera Type	2 Mega Pixel IP Camera
Image Sensor / Encoder Chipset	SONY IMX322 / Amba S233
Lens	DC Auto Iris 2.8~12mm Vari-focal Lens
Total / Effect Pixel	1920(H) x 1080p(V) 30fps
Video Compression	H.264, MJPEG, CBR, VBR support
Video Out	1ch CVBS (NTSC/PAL) / 1ch RJ-45 output
Motion Detection	Support
Ethernet Port	10 / 100 Base-T
Web Application	IE 6 ~ 11, Firefox
Network Protocol	TCP/IP, UDP, SMTP, HTTP, FTP, PPPOE
	DHCP, DNS, DDNS, UPNP, RTP, RTSP
Integration Protocol	ONVIF 2.4 (supported)
Function	2D/3D NR, D-ZOOM, DPC, HLC/BLC, Defog
	D/N, WDR, AGC, AWB
MEDIA CARD (Optional)	
External Storage	Support SD/SDHC CARD, USB 2.0 HOST
Output	VIDEO - HDMI(1080p) / AUDIO - L/R, HDMI
VIDEO Format	RM, RMVB, AVI, DVIX, MKV, MOV, HDMOV, MP4, M4V, PMP, AVC, FLV, VOB, MPG, DAT, MPEG, TS, TP, M2TS, WMV, H.264, H.263, WMV9, VC-1, MPEG1/2/4
VIDEO Resolution	1080P @60Hz
AUDIO Format	MPEG1/2/4, MP3, WMA, OGG, AAC, FLAC, APE, AC-3, DTS, ATRAC, WAV, PCM
Image Format	JPEG, TIF, PNG, BMP
VIDEO Play Control	AUTO, REPEAT, ZOOM, RESUME, TIME

Contact ViewZ

- Address : 177 W. Orangethorpe Ave., Placentia, CA 92870
- Phone : (714) 996-1177, Fax : (714) 996-1138
- Sales : sales@viewzusa.com
- Specification subject to change without notice.