

1080p Penta-brid HDCVI DVR

16-Channel 1U Digital Video Recorder with Analytics+



Wiz Sense

WizSense Series devices combine Dahua's powerful Analytics+ with an intuitive and easy to use interface. WizSense devices offer Smart Motion Detection and Perimeter Protection functions that focus on human and vehicular images and ignore irrelevant images to capture important video while reducing false alarms. WizSense Series devices provide powerful general surveillance for small to medium size businesses at a sensible price.

System Overview

The X52B Series HDCVI DVR offers high-definition recording on each HDCVI channel and a host of advanced features and functions. The X52B takes advantage of HDCVI technology for easy integration into existing video surveillance systems while leveraging existing networks, cabling, and cameras. Penta-brid access technology seamlessly records video from HDCVI, AHD, TVI, CVBS, and IP sources simultaneously. This recorder is the ideal solution for actively monitoring public venues, retail stores, transportation hubs and access ways, personal property and homes, and educational institutions.

Functions

Perimeter Protection

Dahua Analytics+ includes Tripwire and Intrusion functions that offer custom tripwires based on object type for automation in limited access areas. Perimeter Protection requires less pixels to detect an object to deliver improved accuracy and decreased false alarms due to lights, weather, trees, or animals.

Smart Motion Detection

The Smart Motion Detection, a component of Dahua's Analytics+ technology, improves alarm accuracy and decreases the number of false alarms. The advanced SMD algorithm analyzes a scene for human or vehicle motion, while filtering out other motion due to trees, leaves, animals, weather, and triggers an alarm when detected.

- 5M-N/1080p Recording Resolution on All HDCVI Channels
- Available with a 4 TB, 6 TB, 8 TB, or 10 TB Pre-installed Hard Drive
- Dual-stream Video Recording
- AI Coding Technology for High-quality Human/Vehicle Video
- Auto-detection and Auto-configuration of Video Inputs
- 16 + 8 IP Camera Channels, each channel up to 6 MP
- Maximum 128 Mbps Incoming Bandwidth
- Perimeter Protection and Smart Motion Detection (SMD)
- Long-distance Video Transmission
- Five-year Warranty*



AI Coding

The AI Coding function puts recording emphasis on human or vehicular objects in the video scene. This technology, based on constant bit rate (CBR), dynamically allocates increased bit rate to the target object while reducing the bit rate allocated to background objects. AI Coding reduces bit rate and storage requirements by up to 50% when compared to the H.265 video compression standard.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 90% when compared to the H.264 video compression standard.

HDCVI/AHD/TVI/CVBS Auto-detect

The HDCVI DVR automatically recognizes the incoming signals of each attached camera without any setup, making installation easy and operation convenient.

Long Distance Transmission

HDCVI technology guarantees real-time transmission over long distances without loss of video quality. HDCVI devices provide the same resolution as most IP network camera systems using existing RG-59, RG-6, or CAT 6 UTP cabling.

Technical Specification	
System	
Main Processor	Embedded Processor
Operating System	Embedded LINUX
Analytics+ Perimeter Protection ¹	
Performance	<ul style="list-style-type: none">• Human and Vehicle object classification• Decreased false alarms from leaves, lights, animals• Configure function on two (2) channels, or configure function on one (1) channel to use seven (7) channels for SMD• 10 Tripwire/Intrusion rules per channel
Live View	<ul style="list-style-type: none">• Configure Rule and Object Inspection area• Display object classification, event types, trigger time, image snapshot, and object types• Export event playback 10 seconds prior to or after event
Playback	<ul style="list-style-type: none">• Search by channel, time, event type, and target type• Search event playback 10 seconds prior to or after event• Snapshot capacity: 500,000

Analytics+ Smart Motion Detection ¹	
Performance	<ul style="list-style-type: none">• Detect motion based on object classification (human or vehicle)• Decreased false alarms from leaves, lights, animals• Configure functions on 16 channels, or configure functions on seven (7) channels to use one (1) channel of Perimeter Protection
Preview	<ul style="list-style-type: none">• Configure and inspect detection area
Playback	<ul style="list-style-type: none">• Search by channel, time, event type, and target type• Search event playback 10 seconds prior to or after event

Interface		
Analog Camera Input		16 Channels, BNC
HDCVI		5 MP, 4 MP, 1080p, 720p
AHD		5 MP, 4 MP, 3 MP, 1080, 720p
TVI		5 MP, 4 MP, 3 MP, 1080, 720p
CVBS		NTSC
IP Camera Input		16+8 Channels, each channel up to 6 MP (The recording rate is dependent on the maximum resolution and frame rate of the connected IP camera.)
Audio		Input: Four (4) Channels, RCA Output: One (1) Channel, RCA
Two-way Talk		Audio Input Channel 1 In/ Audio Output, RCA
Recording		
Compression		AI Coding, Smart H.265+, H.265, Smart H.264+, H.264
Recording Resolution		5M-N, 4M-N, 1080p, 1080N, 720p, 960H, D1, CIF
Record Rate	Main Stream	5M-N at 10 fps 4M-N, 1080p at 15 fps 1080N, 720p, 960H, D1, CIF at 30 fps
	Sub Stream	960H at 15 fps; D1, CIF at 30 fps
Max. Incoming Bandwidth		128 Mbps
Bit Rate		32 Kbps to 6144 Kbps per Channel
Record Mode		Manual, Schedule (Regular, Continuous), MD (Video Detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Record Interval		1 to 60 minutes (default: 60 minutes), Pre-record: 1 s to 30 s, Post-record: 10 s to 300 s
Audio Compression		G.711a, G.711u, PCM
Audio Sample Rate		8 KHz, 16 bits per Channel
Audio Bit Rate		64 Kbps per Channel

Display		
Interface		One (1) HDMI (3840 x 2160) One (1) VGA (1920 x 1080)
Spot Output		HDMI: 1920 x 1080,1280 x 1024, 1280 x 720 VGA: 1920 x 1080,1280 x 1024, 1280 x 720
Native Output Resolution	HDMI ²	3840 x 2160, 2560 x 1440, 1920 x 1080, 1280 x 1024, 1280 x 720
	VGA	1920 x 1080, 1280 x 1024, 1280 x 720
Maximum Playback Decoding		16 Channels of 4 M-N at 15 fps 16 Channels of 1080p at 15 fps Eight (8) Channels of 1080p at 30 fps Four (4) Channels of 4 M-N at 30 fps
Multi-screen Display		IP extension mode disabled: 1/4/8/9 IP extension mode enabled: 1/4/8/9/16
Fisheye Dewarp		Supported via Web Interface
On-screen Display		Camera Title, Time, Video Loss, Camera Lock, Motion Detection, Recording

Network	
Interface	One (1) RJ-45 (1000 Mbps) Port
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,DDNS, FTP, Alarm Server, P2P, IP Search (Supports Dahua IP cameras, DVRs, NVS)
Maximum User Access	128 Users
Mobile Operating System	IOS, Android
Interoperability	ONVIF 16.12, CGI Conformant

Video Detection and Alarm	
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 x 18), Video Loss, Tampering, and Diagnosis
Alarm Input	16 Channels
Relay Output	Three (3) Channels

Playback and Backup	
Playback ³	1/4/9/16
Search Mode	Time/Date, Alarm, MD and Exact Search (accurate to 1 second)
Playback Function	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, and Digital Zoom
Backup Mode	USB Device/Network

Storage	
Internal HDD	Two (2) SATA Ports, up to 10 TB capacity for each disk

Auxiliary Interface	
USB	One (1) USB 2.0 Port and One (1) USB 3.0 Port
RS485	One (1) Port for PTZ Control

Electrical	
Power Supply	12 VDC, 4 A
Power Consumption	< 12 W, without HDD

Construction	
Dimensions	
HDCVI DVR	1U, 375.0 mm x 278.40 mm x 53.0 mm (14.76 in. x 10.96 in. x 2.09 in.)
with PFH101 Rack Mount Tray	482.6 mm x 287.15 mm x 53.0 mm (19.0 in. x 11.31 in. x 2.09 in.)
Net Weight	1.80 kg (4.0 lb)
Gross Weight	3.10 kg (6.80 lb)
Installation	Desktop or Rack-mount

Video Transmission Distance		
RG-59/U Coax	720p:	800 m (2624.67 ft)
	1080p:	500 m (1640.42 ft)
	4K/4MP:	500 m (1640.42 ft)
RG-6/U Coax	720p:	1200 m (3937.01 ft)
	1080p:	800 m (2624.67 ft)
	4K/4MP:	700 m (2296.59 ft)
CAT 6 UTP (balun required)	720p:	450 m (1476.38 ft)
	1080p:	300 m (984.25 ft)
	4K/4MP:	300 m (984.25 ft)

Environmental	
Operating Conditions	−10° C to +55° C (+14° F to +131° F), 0% to 90% RH
Storage Conditions	−20° C to +70° C (−4° F to +158° F), 0% to 90% RH


Third-party Support	
Third-party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and others

Certifications	
Safety	UL 60950 EN 60950-1 IEC 60950-1
Electromagnetic Compatibility (EMC)	FCC CFR 47 Part 15 Subpart B EN 61000-3-2 EN 61000-3-3 EN 55032 EN 50130 EN 55024

1. The Analytics+ functions are disabled when the additional IP channels are active.
2. The output resolution for HDMI reduces to 1920 x 1080, 1280 x 1024, 1280 x 720 when the SMD function is enabled.
3. The Playback split reduces to 1/4/9 when the SMD function is enabled.

Ordering Information		
Type	Part Number	Description
1080p HDCVI DVR with Analytics+	X52B3A4	16-Channel Penta-brid 1080p 1U, 4 TB Digital Video Recorder
	X52B3A6	16-Channel Penta-brid 1080p 1U, 6 TB Digital Video Recorder
	X52B3A8	16-Channel Penta-brid 1080p 1U, 8 TB Digital Video Recorder
	X52B3A10	16-Channel Penta-brid 1080p 1U, 10 TB Digital Video Recorder
Accessory, optional	PFH101	Rack Mount Tray 482.60 mm x 281.20 mm x 43.7 mm (19.0 in. x 11.07 in. x 1.72 in.)

Rear Panel



1	Ground	7	Audio Output (x1 RCA)
2	Audio Input (x4 RCA)	8	HDMI Output
3	VGA Output	9	USB Port
4	Power Switch	10	RJ-45 Ethernet Port (1000 Mbps)
5	Alarm Input (x16) Alarm Output (x3)	11	Power Input
6	Video Input (x16 BNC)	12	RS485 Port

