



1080P Day & Night Auto Focus IR Bullet IP Camera



Features

- Full HD 2 megapixel CMOS image sensor
- 1080P True H.264 AVC High Profile video compression
- H.264 and Motion JPEG multi-profile video streaming
- Auto focus with zoom / focus motorized lens
- 3D noise reduction (MCTF)
- 2D WDR function HDR function up to 100dB
- Digital PTZ supported
- IVS supported
- Motion detection, Tampering detection, audio detection, tripwire, object counting, traffic light detection function
- Smart event support
- High efficiency IR LED, radiant distance up to 35M
- Day & Night (IR cut removable)
- 2-way audio supported
- Digital I/O : 1 in, 1 out
- ONVIF Profile S supported
- IP68 rain and dust resistant

Specifications

Model	ZFR8122EX2
Min. illumination/Low Light Mode (Colour)	Color : 0.06 Lux at F1.8 ; B/W : 0.005 Lux at F1.8 ; 0 Lux with IR LED ON
Starting Temperature	-10°C – +50°C (14°F – 122°F)
Operating temperature	-40°C – +50°C (-40°F – 122°F)
Storage temperature	-25°C – +60°C (-13°F – 140°F)
Operating humidity	0% – 90% RH
Power Supply	DC12V ±10% / PoE+ (IEEE 802.3at)
Power Consumption	DC12V, 15.8W / PoE+, 18.8W
Lens	7.0 – 22 mm (zoom / focus motorized)
Iris	F1.8(W) – F2.8(T)
Iris Control	DC-IRIS
Angle of View	41° (W) – 14° (T)(H) 22° (W) – 8° (T)(V) 48° (W) – 18° (T)(D)
Peak wavelength	850nm
Beam Spread	60°, 90°
Max IR distance	35M
Pick Up Element	1/2.86" MOS image sensor
Effective pixels	1944 (H) × 1213 (V) = 2,358,072 (pixels)
CE	Yes, EMI CLASS A
FCC	Yes, EMI CLASS A
IP Rating	IP68
Vandal Resistant Rating / IK Rating	IK10
CPU requirement	Intel® Core™ i5 or higher grade
OS requirement	Windows 7 or above
RAM	8GB or above, Dedicated Graphics Card
Web browser	Microsoft® Internet Explorer® 9 or above
Dimensions	102.5(W) × 102.5(H) × 258(D) mm
Weight	1050g approx
Window / Glass Thickness	Ø75 Heat Resistant Glass & Rain repellent glass

Audio Input / Output	Mono, 1.98 Vp-p , 2.2KΩ , Terminal Block
Audio	Two-way Audio, G.711 u-law / PCM / AAC, External Microphone Required
Alarm Input / output	Digital 1 input (TTL, +3 – 5VDC) / 1 Output (MOS Relay contact N.O., Load max. 40VDC/300mA)
Live Video Output	CVBS 1.0Vp-p, 75 ohm, RCA connector
Video Compression	8GB or above, Dedicated Graphics Card
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.264 and Motion JPEG, configurable frame rate, bandwidth Codec and GOP
Number of streams	4
Video bitrate	128Kbps – 12Mbps; Frame rate and bit rate controllable on-the-fly; VBR / CBR / GOP supported; Fixed bitrate
Encryption	Base64 HTTP encryption, HTTPS encryption
Authentication	Digest HTTP authentication, RTSP authentication, 802.1x, DDNS via HTTPS
Address Filter	IP address filter, MAC address filter
Access	Multiple user access levels with password protection
User accounts	10 simultaneous users
Multi IP address	Yes
Resolution	2MP(1920 × 1080), 1.3MP(1280 × 960), 1MP(1280 × 720), D1(720 × 480, 720 × 576), VGA(640 × 480), CIF(352 × 240)
Frame Rates	"Single-stream mode, H.264 : up to 120 fps @ 1920 × 1080 (Video only support preview mode) Multi-stream mode, H.264 : up to 60 fps @ 1920 × 1080, MJPEG : up to 30 fps @ 1920 × 1080 HDR mode, H.264 : up to 30 fps @ 1920 × 1080 , MJPEG : up to 30 fps @ 1920 × 1080"
Scanning System	Progressive Scan

Infrared Cut Filter	Auto / Day (Color) / Night (Mono) / Schedule
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Custom
Back Light Compensation (BLC)	On/Off
Electrical Shutter	1/30(1/25)s – 1/30000s
Sense Up	Off / 1 Frame / 2 Frames
Sense Up+	Yes
Auto Gain Control	60 dB Variable Gain
S / N Ratio	More than 50dB (AGC off)
3D Noise Reduction	Off / 1 – 32 Selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode)
High Dynamic Range(HDR)	Up to 120dB (by HDR mode, 2 shutter line interleave)
Privacy Masking	Off / On (4 zones)
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip, Defog
Auto Focus	One Push
Smart IR	Off / On
Mobile phone	Integrated to LILIN mobile app (LILIN Viewer) iPhone, iPad, Android support
Video Management	ONVIF Profile S, LILIN Navigator Enterprise 2.0, Third party VMS through LILIN HTTP API
SD Card (recording)	Support Micro SD/SDHC/SDXC card for circular recording (card is not included)
Firmware	Firmware update via HTTP and IP Scan; Firmware available at web site
IVS Advanced 2.0	Motion Detection, Tampering Detection, Advanced Motion Detection, Traffic Light Detection, Tripwire Detection, Object Counting
IVS Advanced 2.1 (Optional)	Unattended Object Detection, Missing Object Detection, Crowd Detection, Loitering Detection, Face Detection

Alarm event triggers	Motion / Tamper / Audio / Alarm / Network lost detection
Alarm event actions	FTP / SMTP / HTTP post / SD card / SAMBA / SMTP Trap / Alarm Output
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
Network Interface/Ethernet	10/100/1000 Mbps Base-T, RJ-45
ePTZ & Digital Zoom	Yes, ROI (Region of Interest)
OSD	Text overlay for date, time, and camera name
CPU.Memory	Embedded SoC, 1.0GHz Dual ARM Cortex-A9 & 600MHz ARM11, 1GB DDR3, 256MB flash memory
OS	Linux 3.8.8
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, SIP, MQTT, QoS, SNMP, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SDDP, Bonjour, 802.1x, SSL/TLS
Max number of online users	10 simultaneous users
Video Display	LILIN Universal ActiveX & HTML5